

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 861)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 9, 10, 15, & 16, marked T21S, S 10 on NE, R8W, S 15 on SE, S 16 on SW, S 9 on NW face with 4 notches on S and 3 on E edge from which:

Maple, 6" dia., bears N.45°E., 36 lks., mkd: T21S R8W S10 BT.

Maple, 8" dia., bears S.50°E., 48 lks., mkd: T21S R8W S15 BT.

Maple, 12" dia. bears S.70°W. 27 lks. mkd: T21S R8W S16 BT
Fir, 70" dia., bears N.45°W., 20 lks., mkd: T21S R8W S9 BT

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11399)

The cor. of secs. 9, 10, 15, & 16, the locus of which is determined by reference to the record measurements from the SW & NW BTs.

At the corner point,

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, for cor. of secs. 9, 10, 15, & 16 with brass cap marked:

T21S R8W
S 9|S 10
S 16|S 15

1945 from which

A dead Maple, 16" dia., bears S.67°W., 27 lks., with partial scribe marks on charred face of old blaze (OBT)

A dead Fir, 72" dia., bears N.45°W., 20 lks., with partial scribe marks on charred face of old blaze. (OBT)

A Fir, 48" dia., bears N.39½°E., 102 lks., mkd: T21S R8W S10 BT. (New BT)

A Fir, 44" dia., bears S.40°E., 30 lks., mkd: T21S R8W S15 BT. (New BT)

A Fir, 44" dia., bears S.2°W., 60 lks., mkd: T21S R8W S16 BT. (New BT)

A Fir, 48" dia., bears N.4°W., 243 lks., mkd: T21S R8W S9 BT. (New BT)

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12581)

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12581)

The cor. of secs. 9, 10, 15, & 16, monumented with an iron post 2" dia., 8" above ground, firmly set, with brass cap properly marked

- from which the remains of BTs,
 - A stump hole, bears N.39½°E., 102 lks. (Price BT)
 - A sawed & partly burned fir stump, 47" dia., bears S.40°E., 30 lks., with partial scribe marks visible on burned blaze. (Price BT)
 - A sawed & burned fir stump, 45" dia., bears S.2°W., 60 lks., with blaze healed. (Price BT)
 - A burned Maple stump, 12" dia., bears S.67°W., 27 lks., with no marks remaining. (Wright BT)
 - A sawed & burned fir stump, 60" dia., N.45°W., 20 lks., with no marks remaining. (Wright BT)
 - A sawed & burned fir stump, 50" dia., N.4°W., 243 lks., with illegible scribe marks visible on burned blaze. (Price BT)

- and reference monuments set in present resurvey,
 - An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears N.22½°E., 20 lks., with brass cap marked T21S R8W S10 RM 1954 and an arrow point to the corner.
 - An iron post, 3 ft. long, 2" dia., set 28" in the ground, for a reference monument, bears S.22½°W., 20 lks., with brass cap marked T21S R8W S16 RM 1954 and an arrow point to the corner.

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Fd. Ok by Dan Baker, 10/1984 M 97-51

Clyde Mulkins - for: I.P. Timberlands - Aug. 20, 95 - M 122-77

Found - 1945 GLO 2½" brass cap
72" Orig. D.Fir stump, with no marks, bears N.43°W., 18' to face.
44" Orig. D.Fir stump, bears S.42°E., 20.1'
continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Cor. Secs. 9, 10, 15, & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

44" Orig. D.Fir stump, bears S.1°E., 40.2'
48" Orig. D.Fir stump, bears N.4°W., 161'
6' steel post beside corner
New BTs- 22" D.Fir, bears N.48°E., 7.4', scribed "S 10 BT"
14" D.Fir, bears S.19°E., 11.2', scribed "S 15 BT"
13" Maple, bears S.40°W., 39.3', scribed "S 16 BT"
15" D.Fir, bears N.68°W., 26.5', scribed "S 9 BT"
6' alum post beside corner w/ "Land Survey Monument"
sign.

Found OK by R. Rice, Oct. 2002 - M141-12