

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 862)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on W face from which:

Fir, 14" dia., bears N.54°E., 23 lks., mkd: 1/4 S BT.

Fir, 14" dia., bears N.85°W., 45 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11400)

The 1/4 sec. cor., the locus of which is determined by reference to the record bearing & distance from each of the old BTS.

At point for corner,

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, for 1/4 sec. cor., with brass cap marked:

S 9 | S 10

1945

from which

An uprooted Fir, 20" dia., bears N.54°E., 23 lks., with blaze healed. (OBT)

A Fir, 20" dia., bears N.85°W., 45 lks. mkd: 1/4 S BT. (OBT)

A Fir, 30" dia., bears S.20°E., 59 lks., mkd: 1/4 S10 BT. (New BT)

A Fir, 38" dia., bears N.89°W., 67 lks., mkd: 1/4 S9 BT. (New BT)

BLM remonumentation of an orig. corner point by Norman J. McDonald, Cadastral Surveyor, under Group # 350, surveyed April 30, 1963 - (DCSO records Vol. 33 Page(s) 13657)

The 1/4 sec. cor. of secs. 9 & 10, determined at record bearing & distance from the 1883 BTs:

A down Fir, 25" dia., N.54°E., 23 lks., with scribe marks 1/4 S BT visible on opened blaze.

A Fir, 14" dia., bears N.85°W., 45 lks., with scribe marks 1/4 S visible on partially healed blaze.

and 1945 BTs

A Fir, 33" dia., bears S.20°E., 59 lks., with a healed blaze.

A Fir, 41" dia., bears N.89°W., 67 lks., with a healed blaze.

The 1945 iron post is lost.

At the corner point

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set an iron post, 28" long, 2½" dia., 24" in the ground, with
brass cap marked:

T21S R8W

¼

S 9|S 10

1963

from which a new BT

A Hemlock, 23" dia., bears N.72 3/4°E., 122 lks., mkd: ¼
S10 BT.

Fd. Ok on BLM remonumentation of certain orig. corner points
by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under
group #s 350 & 635, surveyed April/May 1967 - (DCSO records
C.S. File 65/27-1) ** also set a 6 ft. steel fence post
alongside the iron post.**

Fd BC & 4 BTs by D. Baker 10/1984 - M97-51 & C.S. 58/289-3I