

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 862-3)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 3, 4, 9 & 10, marked T21S, S 3 on NE, R8W, S 10 on SE, S 9 on SW, S 4 on NW face with 5 notches on S & 3 on E edge from which:

- Fir, 10" dia., bears N.38°E., 21 lks., mkd: T21S R8W S3 BT
- Fir, 8" dia., bears S.64°E., 41 lks., mkd: T21S R8W S10 BT
- Fir, 10" dia., bears S.72°W., 40 lks., mkd: T21S R8W S9 BT
- Fir, 10" dia., bears N.77°W., 16 lks., mkd: T21S R8W S4 BT

BLM dependent resurvey by Norman D. Price, Cadastral Eng. & Geo. F. Rigby, Assoc. Cadastral Eng., under group #282, surveyed May/Aug. 1945 - (DCSO records Vol. 27 Page(s) 11400)

The cor. of secs. 3, 4, 9 & 10, the almost disintegrated remains of a wooden stake on which no marks remain.

At point for corner,

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with the decayed remains of wooden stake deposited at the base, for cor. of secs. 3, 4, 9, & 10, with brass cap marked:

T21S R8W
 S 4 | S 3
 S 9 | S 10

1945

from which

- A Fir, 24" dia., bears N.39°E., 22 lks., with blaze healed. (OBT)
- A Fir, 18" dia., bears S.63½°E., 34 lks., with partial scribe marks visible on old blaze which has been opened up. (OBT)
- A Fir, 14" dia., bears S.70°w., 39 lks., with blaze healed. I re-blaze & re-mark this old BT T21S R8W S9 BT
- A Fir, 24" dia., bears N.80°W., 16 lks., with blaze healed. I re-blaze & re-mark this OBT T21S R8W S4 BT.
- A Fir, 24" dia., bears S.69°E., 40 lks., mkd: T21S R8W S10 BT. (New BT)

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Fd BC & 4 BTs by D. Baker 10/1984 - M97-51 & C.S. 58/289-3N

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias	Description

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20745-6)

The cor. of secs. 3, 4, 9, and 10, monumented with an iron post, 2" dia., firmly set, projecting 2" above the ground, with brass cap (properly) mkd. from which the remains of the original bearing trees
A fir stump, 24" dia., bears N.39°E., 14.5 ft., no scribe marks visible on open blaze.
A root hole, with remains of a decayed fir inside, bears S.70°W., 25.7 ft.
A fir stump, 24" dia., bears N.80°W., 10.6 ft., with scribe marks BT visible on opened blaze.
and remains of a bearing tree mkd. by Price and Rigby
A fir stump, 28" dia., bears S.69°E., 26.4 ft., no marks visible.
and new bearing trees
A fir, 11" dia., bears N.70½°E., 15.5 ft., mkd. T21S R8W S3 BT.
A fir, 12" dia., bears S.29°E., 30.2 ft., mkd. T21S R8W S10 BT.
A fir, 13" dia. bears S.68°W. 29.8 ft. mkd. T21S R8W S9 BT
A fir, 10" dia., bears N.31½°W., 23.6 ft., mkd. T21S R8W S4 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

The cor. of secs. 3, 4, 9, & 10, remonumented by Price & Rigby in 1945, utilized by Lytle, et ci., in 1952-54, and by Glenn, et al.. in 1967, rehabilitated by Baker, PLS No. 1978, in 1984, and by Graham in 1999-2000; monumented with an iron post, 2" dia., firmly set, projecting 3" above ground, with a brass cap, oriented W., (properly) mkd. from which the remains of the original BTs
A decayed fir stump, 37" dia., bears N.39°E., 14.5 ft., with the bottom of a healed blaze.
A roothole bears S.70°W., 25.7 ft., alongside of which are decayed fir remains.
A decayed fir stump, 24" dia., bears N.80°W., 10.6 ft., with scribe marks BT visible on open blaze.
and the remains of a BT mkd. by Price and Rigby
A decayed fir stump, 30" dia., bears S.69°E., 26.4 ft., with burned remains of a healed blaze.
and the bearing trees mkd. by Graham

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 14" dia., bears N.70½°E., 15.5 ft., with a healed blaze.

A fir, 15" dia., bears S.29°E., 30.2 ft., with a healed blaze.

A fir, 16" dia., bears S.68°W., 29.8 ft., with a healed blaze.

A fir, 13" dia., bears N.31½°W., 23.6 ft., with a healed blaze.

A steel fence post with an International Paper Company tag is alongside the cor.

Corner is located on the flat top of a knob, N.65°W., 25 ft. from the center, and E., 250 ft., from Paradise Creek Road, graveled surface, 15 ft. wide, bearing N.30°W. and S.30°E.