

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION WC So 1/4 Cor Sec 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan. 22, 1881 (DCSO records Vol. 2 Page(s) 836)

Marked a Fir tree for ¼ sec. corner, 12" dia., from which
Fir tree 16" dia., bears N.35°E., 15 lks.
Fir tree 24" dia., bears S.5°E., 40 lks.

GL0 resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12547-48)

AT 38.77 CHAINS:

Point for witness cor. to the ¼ sec. cor. of sec. 34 only.
Set an iron post, 3 ft. long, 1" dia., 27" in the ground,
with brass cap marked: WC ¼ S 34
1952

from which

- A Fir 27" dia., bears N.54½°E., 39 lks. dist. mkd. WC ¼ S34 BT.
- A Fir 34" dia., bears N.34°W., 56 lks. dist. mkd. WC ¼ S34 BT.

AT 38.80 CHAINS - N.89°29'W.

Point for the ¼ sec. cor. of sec. 34 only, a Fir 25" dia., with healed scars facing NE. and NW., from which the original bearing trees:

- A Fir 35" dia., bears N.27¼°E., 17 lks. dist., mkd. ¼ S BT in bark. (Rec. N.35°E., 15 lks. dist.)
- A Fir 50" dia., bears S.11°45'W., 41 lks. dist. mkd. ¼ S BT in bark. (Rec. S.5°E., 40 lks. dist.)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Wm. Stoffel, crew - Sept. 1963 - C.S. File 52/14-32

Found - Brass cap set in 1952
Sawed stump of 27" Fir N.54½°E., 25.7 ft. shows good scar.
No trace of NW BT.
Fir tree at ¼ corner, 2 ft. West of Wit. Cor., alive and in good condition shows good scars.
50" Fir S.11 3/4°W., 27.1 ft. alive and in good condition. Traces of bark scribing visible.
Stump of 35" Fir N.27¼°E., 11.2 ft. bark scribing visible.

(Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 34 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>New BT - 12" Hemlock S.17°E., 15.2 ft. (from brass cap) mkd. ¼ S34 CS BT. No lives trees available North of line. Corner lies on top of ridge, just South of South edge of logging road.</p>
<p>Survey by Les Roberts - For: International Paper Co. - June 1986 - M 102-18 C.S. File 63/18-5(K) ----- Found - 1952 GLO brass cap set firmly in ground mkd. W.C. 30" Corner tree bears West, 1.98 ft. 24" Fir stump bears N.54°E., 25.2 ft., scribe visible. 1952 BT. Rec. N.54½°E., 25.7 ft. New BT - 8" Fir bears N.17°W., 12.6 ft., scribed/painted red. Set metal fence post with survey attention sign wired to, beside brass cap. Corner lies on South slope about 50 ft. South of old dirt logging road.</p>
<p>Greg Lang - Jan. 2005- C.S. File 65/54-2 ----- Found - Brass Cap Witness corner and it's Bearing Trees; A 28" Fir stump bears N.54°E., 25.13' (N.54½°E 25.74' per 1952 resurvey) (N.54°E., 25.2' per 1963 renewal) A 10½" D. Fir bears N.18¼°W., 12.80' (N.17°W., 12.6' per 1986 renewal) The true corner which is a 35" D.Fir bears N89°29'W 2.88 feet (N89°29'W 1.98' per 1952 resurvey) New - A 14½" D.Fir bears N.66½°E., 19.70' from the brass cap witness corner and is marked "X" "BT" A 8" D.Fir bears S.11½°E., 16.90' from the brass cap witness corner and is marked "X" "BT" A 17½" D.Fir bears S.42½°W., 56.80' from the brass cap witness corner and is marked "X" "BT" Note - Corner is located on a south slope, 300' southeasterly of a rock road.</p>
<p style="text-align: right;">2</p>