TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 859)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ S on N face from which:
Fir, 6" dia., bears N.37°W., 50 lks., mkd: ¼ S BT.
Fir, 4" dia., bears S.30°E., 50 lks., mkd: ¼ S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12574)

Point for the ¼ sec. cor. of secs. 22 & 27, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 20" in the ground to solid rock & in a mound of stone to top, with brass cap marked:

¼ $\frac{\text{S 22}}{\text{S 27}}$

from which
A Fir, 10" dia., bears N.11°W., 17 lks., mkd: ¼ S22 BT.
A Hemlock, 30" dia., bears S.5°W., 35 lks., mkd: ¼ S27 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20745)

The ¼ sec. cor. of secs. 22 and 27, monumented with an iron post, 1" dia., firmly set, projecting 14" above the ground, with brass cap (properly) mkd.
from which new bearing trees
A fir, 12" dia., bears N.57¾°E., 19.8 ft., mkd. ¼ S22 BT.
A fir, 9" dia., bears S.46°E., 24.1 ft., mkd. ¼ S27 BT.