

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 860)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on N face from which:

Fir, 6" dia., bears N.25°E., 48 lks., mkd: 1/4 S BT.

Fir, 6" dia., bears S.15°W., 50 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12576)

Point for the 1/4 sec. cor. of secs. 15 & 22, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 $\frac{S\ 15}{S\ 22}$
1954

from which

An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears N.20°W., 50 lks. with brass cap marked 1/4 S15 RM 1954 and an arrow pointing to the corner.

An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears S.20°E., 50 lks. with brass cap marked 1/4 S22 RM 1954 and an arrow pointing to the corner.

Gary Smither - 12/2005 - C.S. File 65/54-41

Found - BLM 1954 brass cap on iron pipe firmly set with steel fence post driven alongside the corner.

BLM 1954 brass cap reference monument at N.20°W., 33.0 ft.

BLM 1954 brass cap reference monument at S.20°E., 33.0 ft.

New - 22" D.Fir S.84°W., 7.0 ft. to spike side center scribed "T21 R8 1/4 S22 BT" with new BT tag.

16" D.Fir N.49°E., 9.8 ft. to spike side center scribed "T21 R8W 1/4 S15 BT"