

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 862)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on N face from which:

Fir, 8" dia., bears N.10°W., 50 lks., mkd: 1/4 S BT.

Fir, 7" dia., bears S.41°E., 13 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12580-1)

Point for the 1/4 sec. cor. of secs. 10 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 S 10
 S 15
 1954

from which

A Cedar, 18" dia., bears N.6 1/2°W., 110 lks., mkd: 1/4 S10 BT.

A Cedar, 13" dia., bears S.73 1/2°W., 76 lks., mkd: 1/4 S15 BT.

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Daniel W. Baker, LS #1978 - For: International Paper Co. - Oct. 25, 1984 - M 97-51 & C.S. File 58/289-3L

Found - 1" Iron pipe with GLO brass cap "1954"

21" Cedar stump, N.5°W., 71.5 ft. (scribe visible - 1954 BT)

New BT - 8" Fir, N.4°W., 45.2 ft. (scribed 1/4 S10 BT)