

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2285, surveyed Aug. 2009/ Feb. 2010 (DCSO records BLM plat 2011 & Vol. 56 Page(s) 22263-65)

The 1/4 sec. cor. of secs. 3 & 10, reestablished by Lytle, et al., in 1952-54, utilized by Glenn, et al., in 1967. and by Baker, PLS No. 1978, in 1984; monumented with an iron post. 1" dia., firmly set, projecting 12" above ground, with a brass cap (properly) mkd, from which the remains of the BTs mkd. by Lytle. et al.

A fir stump, 36" dia., bears N.7¾°E., 27.1 ft. with healed blaze at waist height.

A scarred fir, 15" dia., bears S.20¾°W., 19.8 ft., with healed blaze at knee height and other healed blazes. (Record, S.22¼°W.)

and a reference established by person(s) unknown and reported by Baker, PLS No. 1978

A rusty Iron post, 1½" dia., firmly set, projecting 13", above ground, bears S.40°17'52"E.. 4.06 ft.

and a new BT

A fir, 12" dia., bears N.79°E., 36.3 ft., mkd. ¼ S3 BT. Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

A steel fence post with a U.S. Forest Service tag and two International Paper Company tags is alongside the cor.

Corner is located at the center of the N. edge of a triangular patch of a dozen mature fir trees In otherwise dense fir reproduction.