

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & 34 of T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 453)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor., marked ¼ S on N. face; from which
Fir 8" dia., bears N.15°E., 8 lks. dist. mkd. ¼ S BT.
Fir 8" dia., bears S.5°W., 20 lks. dist. mkd. ¼ S BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11328)

The ¼ sec. cor., determined at the record distance from the original NE. bearing tree and the record bearing and distance from the original SW. bearing tree as follows:

A dead Fir 10" dia., bears N.18°E., 8 lks. dist., with the scribe marks ¼ S visible on the partly opened blaze. (Rec. brg. N.15°E.)

A Fir 20" dia., bears S.5°W., 20 lks. dist. with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

¼ $\frac{S\ 34}{S\ 3}$
1950

from which a new bearing tree:

A Fir 20" dia., N.15°E., 16 lks. dist. mkd. ¼ S34 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16705-06)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 12" above ground with brass cap mkd. in 1950,

from which the remains of the original bearing trees:

A Fir stub 10" dia., bears N.18°E., 8 lks. dist. no marks remaining on burned blaze.

A burned and dead Fir 26" dia., bears S.5°W., 20 lks. dist., with healed blaze.

and the remains of the bearing trees mkd. in 1950:

A burned and dead Fir 25" dia., bears N.15°E., 16 lks. dist. with healed blaze.

Set a 6 ft. steel fence post alongside the iron post.

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Survey by Daniel W. Baker, LS #1978 - For: International Paper Co. - Oct. 25, 1984 - M 97-51 and CS File 58/289-3A

Found - 24" Fir stump N.17°E., 10.5 ft., scribe visible, 1950 BT.

28" Fir stump S.6½°W., 12.5 ft., cut below scribe, original BT.

RESET 1" Iron pipe with GLO brass cap, "1950" at slope distance from existing BTs.

1/2" Rebar driven in center of BT stumps and 4" x 4" post found East, 0.5 ft. from corner point.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21745)

The ¼ sec. cor. of secs. 3 & 34, monumented with an iron post, 1" dia., firmly set, projecting 1" above the ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A fir stump, 25" dia., bears S.5°W., 12.5 ft. to a rebar, ½" dia., driven in the center of the stump, no marks visible. (Record, 13.2 ft.)

and the remains of a bearing tree mkd. by Tillman in 1950

A fir stump, 25" dia., bears N.15°E., 10.6 ft., to a rebar, ½" dia., driven in the center of the stump, with scribe marks S34 visible on open blaze.

and new bearing trees

A fir, 14" dia., bears S.21°W., 9.6 ft., mkd. ¼ S3 BT.

A fir, 11" dia., bears N.30½°W., 14.9 ft., mkd. ¼ S34 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

There is a tag nearby that reads "This is the second corner Bill Glenn was at starting his survey career 1950 1986."

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2780, surveyed March/Aug. 2015 - (DCSO records Vol. 58 Page(s) 23443-5 & Plat T20-8 2016-1)

The ¼ sec. cor. of secs. 3 & 34, on the S. bdy. of the Tp., monumented with an iron post, 1" dia., firmly set, projecting 1" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir stump, 24" dia., bears S.5°W., 12.5 ft., to a rebar, ¼" dia., driven in the center of the stump by Baker, PLS 1978, in 1984, no marks visible.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 440700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; & 34 of T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and the remains of a bearing tree mkd. by Tillman in 1950
A decayed fir stump, 24" dia., bears N.15°E., 10.6 ft., to
a rebar, ½" dia., driven in the center of the stump by
Baker, PLS 1978, in 1984, with scribe marks S34 BT
visible on open blaze.
and the bearing trees mkd. by Graham in 2005
A fir, 18" dia., bears S.21°W., 9.6 ft., with a healed
blaze.
A fir, 14" dia., bears N.30½°W., 14.9 ft., with a healed
blaze.
A steel fence post is alongside the monument. There is a tag
nearby that reads "This is the second cor. I was at when
started my surveying career June 1950 -- W. W. Glenn".