

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 848)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on W face from which:

Cedar, 20" dia., bears S.88°E., 43 lks., mkd: 1/4 S BT.

Cedar, 40" dia., bears S.65°W., 27 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12568)

Point for the 1/4 sec. cor. of secs. 34 & 35, determined from the OBTs:

A Cedar, 37" dia., bears S.88°E., 43 lks., with nearly healed blaze.

A stump hole of a fallen Cedar, bears S.65°W., 27 lks.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap marked:

1/4
S 34|S 35
1952

from which

A Fir, 62" dia., bears S.20 1/2°E., 94 lks., mkd: 1/4 S35 BT.

A Fir, 40" dia., bears S.47 1/2°W., 57 lks., mkd: 1/4 S34 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20740-1)

The 1/4 sec. cor. of secs. 34 & 35, determined at record distance from the original NE. BT, at record distance from the SW. BT, and record bearing to SE. BT:

from which an original BT

A cedar, 38" dia., bears N.86 1/2°E., 28.4 ft., with a healed blaze. (Record, S.88°E.)

and the remains of BTs mkd. by Lytle, et. all

A fir stump, 60" dia., bears S.20 1/2°E., 58.6 ft., with a healed blaze. (Record, 62.0 ft.)

A fir stump, 41" dia., bears S.53°W., 37.6 ft., with decayed partially opened blaze. (Record, S.47 1/2°W.)

At the corner point

Set a brass tablet, 3 1/4" dia., 3 1/2 in. stem, in bedrock, with top mkd.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T 21 S R 8 W

^¼
S 34 | S 35
 1999

from which new BT

A fir, 17" dia., bears S.35½°W., 22.9 ft., mkd. ¼ S34 BT.

The 1952 1" iron post and brass cap is in a slide area and has slid down hill. It is impractical to bury this monument alongside, therefore I remove it from the area.