

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 848-9)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 26, 27, 34 & 35, marked T21S, S 26 on NE, R8W, S 35 on SE, S 34 on SW, S 27 on NW face with 2 notches on E & 1 on S edge from which:

- Fir, 12" dia., bears N.80°W., 70 lks. mkd: T21S R8W S27 BT
- Laurel, 6" dia, bears S.66°W. 30 lks. mkd: T21S R8W S34 BT
- Laurel, 5" dia. bears N.50°E. 66 lks. mkd: T21S R8W S26 BT
- Laurel, 4" dia. bears S.53°E. 72 lks. mkd: T21S R8W S35 BT

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12569)

Point for the cor. of secs. 26, 27, 34, & 35, determined from the remains of the OBTS:

- A burned & rotted Fir stump, bears N.80°W., 70 lks.
- A Madrona stool, bears N.50°E., 66 lks.
- A Madrona stool, bears S.66°W., 30 lks.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 14" in the ground, to solid rock & in a mound of stone, 3 ft. base, to top, with brass cap marked:

T21S	R8W
<u>S 27</u>	<u>S 26</u>
S 34	S 35
1952	

from which

- A Fir, 27" dia., bears N.60¼°E., 66 lks., mkd: T21S R8W S26 BT.
- A Fir, 20" dia., bears S.20½°E., 113 lks., mkd: T21S R8W S35 BT.
- A Fir, 30" dia., bears S.40½°W., 34 lks., mkd: T21S R8W S34 BT.
- A Fir, 18" dia. bears N.5¼°W. 30 lks. mkd: T21S R8W S27 BT

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20741)

The cor. of secs. 26, 27, 34, & 35, monumented with an iron post, 2" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees mkd. by Lytle, et. all
A fir, 26" dia., bears S.28½°E., 74.6 ft., with a healed blaze. (Record, S.20¼°E.)
A fir, 44" dia., bears S.39¼°W., 22.4 ft., with a healed blaze. (Record, S.40½W.)
A fir, 21" dia., bears N.2½°W., 19.8 ft., with a healed blaze. (Record, N.5¼°W.)
and new bearing tree
A fir, 18" dia., bears N.83¾°E., 35.6 ft., mkd. T21S R8W S26 BT.

Fd as per record - a 6 ft steel post is set 2 ft north - 1/2020 - by D. Edwards - C.S. File 65/105-006