

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 849-50)

-----  
Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on S face from which:

Alder, 4" dia., bears N.42°E., 15 lks., mkd: 1/4 S BT.

Alder, 2" dia., bears S.22°W., 16 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12571-2)

-----  
Point for the 1/4 sec. cor. of secs. 26 & 27, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 26" in the ground with brass cap marked:

1/4  
S 27 | S 26  
1952

from which

A Fir, 25" dia., bears S.2 1/2°E., 37 lks., mkd: 1/4 S26 BT.

A Fir, 30" dia., bears S.30 1/2°W., 15 lks., mkd: 1/4 S27 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22063-4)

-----  
The 1/4 sec. cor. of secs. 26 & 27, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the BTs mkd. by Lytle, et al., in 1952-54

A fir snag, 37" dia., bears S.2 1/2°E., 24.4 ft., with a healed blaze.

A fir, 55" dia., bears S.30 1/2°W., 9.9 ft., with a healed blaze.

and a new bearing tree

A fir, 6" dia., bears S.8 1/4°E., 22.1 ft., mkd. 1/4 S26 BT.

Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.

David Edwards - Crew: Brant Miller & Eric Sprinkle -  
1/13/2020 - C.S. File 65/104-30

-----  
Found - 1952 BLM brass capped iron pipe.

A 55" dia. Fir with healed blaze bears S.30 1/2°W., 9.9 ft. ( 1954 B.T. ) Continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

The 6" dia. Fir from 2007 bears S.8¼°E., 22.1 ft. It is root sprung and leaning badly.  
The Fir snag S.2½2°E., is down.  
New - A 7" dia. Hemlock scribed "¼ S26 BT" bears N.62°E., 6.05 ft.  
A 6 ft steel post is set 2 ft South.  
Note - Compass Declination 15° East

Fd as per record - a 6 ft steel post is set 2 ft south - 1/2020 - by D. Edwards - C.S. File 65/105-006