

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 850)

-----  
Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 22, 23, 27, & 26, marked T21S, S 23 on NE, R8W, S 26 on SE, S 27 on SW, S 22 on NW face with 2 notches on S & E edge from which:

- Alder, 3" dia. bears N.10°E., 16 lks. mkd: T21S R8W S23 BT
- Alder, 4" dia. bears S.80°E., 19 lks. mkd: T21S R8W S26 BT
- Alder, 7" dia. bears S.60°W., 22 lks. mkd: T21S R8W S27 BT
- Alder, 8" dia. bears N.76°W., 27 lks. mkd: T21S R8W S22 BT

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12572)

-----  
Point for the cor. of secs. 22, 23, 26, & 27, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 26" in the ground, with brass cap marked:

T21S	R8W
<u>S 22</u>	<u>S 23</u>
S 27	S 26
1952	

from which

- A Fir, 58" dia., bears N.27°E., 190 lks., mkd: T21S R8W S23 BT.
- A Fir, 30" dia. bears S.29°E. 96 lks. mkd: T21S R8W S26 BT
- A Fir, 25" dia., bears S.27°45'W., 128 lks., mkd: T21S R8W S27 BT.
- A Cedar, 41" dia., bears N.22½°W., 68 lks., mkd: T21S R8W S22 BT.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20742-3)

-----  
The cor. of secs. 22, 23, 26, & 27, determined at record bearing and distance to the NE. BT, & record distance to the SW. BT:

from which BTs mkd. by Lytle, et. all

- A fir, 65" dia., bears N.27°E., 125.4 ft., with a healed blaze.
- A fir, 35" dia., bears S.29½°W., 84.5 ft., with a healed blaze. (Record, S.27¾°W.)

continued next page

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T 21 S R 8 W  
S 22 | S 23  
S 27 | S 26  
1999

from which new bearing trees  
A fir, 7" dia., bears S.75¾°E., 8.0 ft., mkd. X BT.  
A hemlock, 11" dia., bears N.54½°W., 20.9 ft., mkd. T21S R8W S22 BT.  
The corner falls on a steep E. slope.

Ronald Rice, Ward NW INC. - Ben Pastor - Dec. 2002 - C.S. File 65/44-31A&B

-----  
Found - 3" BLM BC marked - T21S R8W S22/S23/S27/S26 1999  
78" D.Fir bears N.27°E. 125.4 ft. healed face. Lytle  
35" D.Fir bears S.29½°W. 84.5 ft. healed face. Lytle  
12" Hem. bears N.54½°W., 20.9 ft., open face. 1999  
7" D.Fir (1999) down out of position.  
New - 10" D.Fir bears N.16°W., 26.3 ft. blazed, scribed "T21S R8W S22 BT"

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22064-5)

-----  
The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.  
from which the BTs mkd. by Lytle, et al., in 1952-54  
A dead top fir, 66" dia., bears N.27°E., 125.4 ft., with a healed blaze.  
A dead top fir, 35" dia., bears S.28½°W., 84.5 ft., with a healed blaze. (Record, S.29½°W.  
and the remains of the BTs mkd. by Graham in 1999-2000  
A roothole bears S.75¾°E., 8.0 ft., with a down fir, 7" dia., alongside with scribe marks X BT visible on open blaze.  
A hemlock, 13" dia., bears N.54½°W., 20.9 ft., with scribe marks T21S R8W S22 BT visible on partially healed blaze and a bearing tree mkd. by Rice, in 2002  
A fir, 11" dia., bears N.13¾°W., 26.2 ft., with illegible scribe marks visible on partially healed blaze and an aluminum nail on the left side center.  
and a bearing tree mkd. by person(s) unknown  
A fir, 63" dia., bears S.3¾°E., 66.6 ft., with axe marks visible. continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor. Secs. 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Aluminum fence post is alongside the cor.  
Corner is located on the SE. cor. of recently logged area,  
edge bears N. and W.  
The geographic position (NAD 1983 (CORS 96)) of the corner of  
sections 22, 23, 26, & 27, as determined by a direct tie from  
a (GPS) observation on a temporary monument processed using  
the National Geodetic Survey's Online Positioning User  
Service (OPUS), is as follows:  
Latitude: 43°43'16.46"N. Longitude: 123°37'21.60"W.