

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 22 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the reference monuments by Lytle, et al., in 1952-54

An iron post, 1" dia., firmly set, with top flush with the surface of the ground, bears N.89°25'10"E., 40.01 ft. with brass cap mkd. ¼ S23 RM 1954 and an arrow pointing to the corner. (Record, East, 39.6 ft.)

An iron post, 1" dia., firmly set, projecting 2" above ground, bears S.89°41'30"W., 39.66 ft., with brass cap mkd. ¼ S22 RM 1954 and an arrow pointing to the corner. (Record, West, 39.6 ft.)

and BTs mkd. by Rice, in 2002

A fir, 27" dia., bears S.44½°E., 24.6 ft., with scribe marks S23 BT visible on partially healed blaze and an aluminum nail on the right side center.

A fir, 19" dia., bears N.11½°W., 14.7 ft., with scribe marks ¼ S22 B visible on partially healed blaze and an aluminum nail on the right side center.

An aluminum fence post is alongside the cor.