

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 851)

-----  
Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 14, 15, 22, & 23, marked T21S, S 14 on NE, R8W, S 23 on SE, S 22 on SW, S 15 on NW face with 3 notches on S & 2 on E. edge from which:

- Alder, 5" dia. bears N.16°E., 19 lks. mkd: T21S R8W S14 BT
- Alder, 3" dia. bears S.22°E., 35 lks. mkd: T21S R8W S22 BT
- Alder, 7" dia. bears S.15°W., 42 lks. mkd: T21S R8W S22 BT
- Alder, 4" dia. bears N.33°W., 71 lks. mkd: T21S R8W S15 BT

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12575)

-----  
Point for the cor. of secs. 14, 15, 22, & 23, proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T21S	R8W
<u>S 15</u>	<u>S 14</u>
S 22	S 23
1954	

from which

- An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears N.45°E., 50 lks. with brass cap marked T21S R8W S14 RM 1954 and an arrow pointing to the corner.
- An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears S.45°W., 50 lks. with brass cap marked T21S R8W S22 RM 1954 and an arrow pointing to the corner.

Troy Rambo - June 2001 - C.S. File 65/37-22A

-----  
Found - 1954 GLO brass cap, from which I found the rec. reference monuments in place.

- Scribed- "S23 BT" on a 13" DF - bears S.70°E., 10.6 ft.
- "S15 BT" on a 18" DF - bears N.33°W., 11.7 ft.

Fd. Ok by Ronald Rice, Ward NW INC. - Ben Pastor - Dec. 2002 - C.S. File 65/44-33

FD. Ok Gary Smither, 12/2005 - C.S. File 65/54-41

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22067)

-----  
The cor. of secs. 14, 15, 22, & 23, monumented with an iron post, 2" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the reference monuments by Lytle, et al., in 1952-54.

An iron post, 2" dia., firmly set, projecting 13" above ground, bears N.45°41'45"E., 32.17 ft., with brass cap mkd. T21S R8W S14 RM 1954 and an arrow pointing to the corner. (Record, N.45°E., 33.0 ft.)

An iron post, 2" dia., firmly set, projecting 4" above ground, bears S.44°53'15"W., 33.68 ft., with brass cap mkd. T21S R8W S22 RM 1954 and an arrow pointing to the corner. (Record, S.45°W., 33.0 ft.)

and BTs mkd. by Rambo, in 2001

A fir, 14" dia., bears S.68°E., 10.5 ft., with illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the left side center.

A fir, 17" dia., bears N.33°W., 11.7 ft., with illegible scribe marks visible on pitched-over partially healed blaze and an aluminum nail on the left side center.

An aluminum fence post is alongside the cor.

Corner is located on the SW cor. of recently logged area, edge bears N & E.