

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 852)

-----  
Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on W face from which:

- Alder, 5" dia., bears N.37°E., 42 lks., mkd: 1/4 S BT.
- Alder, 3" dia., bears S.16°W., 95 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, & Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO recs. Vol 30 Page 12578)

-----  
Point for the 1/4 sec. cor. of secs. 14 & 15, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4  
S 15|S 14  
1954

from which

- An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears S.20°E., 45 lks. with brass cap marked 1/4 S14 RM 1954 and an arrow pointing to the corner.
- An iron post, 3 ft. long 1" dia., set 28" in the ground, for a reference monument, bears N.20°W., 45 lks. with brass cap marked 1/4 S15 RM 1954 and an arrow pointing to the corner.

Gary Smithers - For: Roseburg Resources Co. - Aug. 2006 - M151-44

-----  
Found - 1954 BLM brass cap with two reference monuments  
DCSO recs. Vol 30 pg 12578  
New BTs- 21" D.Fir S.73°W., 3.4 ft. to spike side center  
scribe T21R8 1/4 S15 BT  
15" D.Fir N.27°W., 5.9 ft. to spike side center  
scribe T21R8 1/4 S15 BT.