

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 854)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on W face from which:

Fir, 18" dia., bears S.62°W., 11 lks., mkd: 1/4 S BT.

Fir, 36" dia., bears S.68°W., 9 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12582)

The 1/4 sec. cor. of secs. 10 & 11, determined at record bearing & dist. from the remaining OBT, as follows:

A Fir, 55" dia., bears S.68°W., 9 lks., with the scribe marks BT visible on bark blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

1/4
S 10 | S 11
1954

from which the new BTs,

A Cedar, 30" dia., bears S.54°45'E., 45 lks., mkd: 1/4 S11 BT.

A Cedar, 34" dia., bears N.76 1/2°W., 74 lks., mkd: 1/4 S10 BT.

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Fd. Ok by Dan Baker, 10/1984 - M 97-51 & C.S. 58/289-3J