

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 453-54)

 Set post 6" dia., 4 ft. long, with marked stone, 12" in ground, for cor. to secs. 2, 3, 34 and 35, marked T20S S35 on NE.; R8W S2 on SE.; T21S S3 on SW.; S34 on NW. faces with 4 notches on W. & 2 on East edges; from which
 Fir 30" dia., bears N.82°W., 25 lks. dist. mkd. T20S R8W S34 BT.
 Fir 40" dia., bears S.41°W., 40 lks. dist. mkd. T21S R8W S3 BT.
 Fir 40" dia., bears S.35°E., 27 lks. dist. mkd. T21S R8W S2 BT.
 Fir 6" dia., bears N.92°E., 47 lks. dist. mkd. T20S R8W S35 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #292, Surveyed June/Oct. 1950 - (DCSO records Vol. 27 Page(s) 11327-28)

 The Sec. Cor., determined at the record bearing and distance from the original SE. bearing tree as follows:
 A Fir 50" dia., bears S.35°E., 27 lks. dist. mkd. with a scribe on the bark T21S R8W S2.
 A Fir 40" dia., bears S.44°W., 26 lks. dist., blazed on the bark, but no scribe marks remain. (Rec. brg. S.41°W., 40 lks. dist.)
 A Fir 50" dia., bears N.88°W., 47 lks. dist., with partial scribe marks visible on the bark.

The record calls for:
 A Fir 6" dia., bears N.92°E., 47 lks. dist.
 A Fir 30" dia., bears N.82°W., 25 lks. dist.
 Wright evidently confused these trees when completing the returns.

At the corner point
 Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20	S R 8 W
S 34	S 35
S 3	S 2
T 21 S	
1950	

from which new bearing trees:
 A Hemlock 10" dia., bears N.30°E., 39 lks. dist. mkd. T20S R8W S35 BT.
 A Fir 50" dia., bears S.59¼°W., 59 lks. dist. mkd. T21S R8W S3 BT.

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T20-8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16705)

 The Sec. Cor., monumented with an iron post 2" dia., firmly set, protruding 15" above ground with brass cap mkd. in 1950, from which the remains of the original bearing trees:

A burned Fir snag 55" dia., bears S.35°E., 29 lks. dist., no marks remaining on bark blaze. Rescribed T21S R8W BT on new blaze.

A burned Fir snag 40" dia., bears S.34°W., 30 lks. dist., no marks remaining on bark blaze. (Rec. S.44°W., 26 lks.)

A burned and dead Fir 57" dia., bears N.88°W., 47 lks. dist., no marks remaining on bark blaze. Rescribed T20S R8W S34 BT on new blaze.

and the remains of the bearing trees marked in 1950:

A Hemlock 16" dia., bears N.30°E., 39 lks. dist., no marks remaining on burned blaze.

A burned and dead Fir 60" dia., bears S.59¼°W., 59 lks. dist., with healed blaze.

and a new bearing tree:

A burned and dead Fir 67" dia., bears N.52°E., 55 lks. dist., mkd. T20S R8W S35 BT.

Set a 6 ft. steel fence post alongside the iron post.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew - July 31, 1967 - C.S. File 54/67 - C.S. File

 Found 1950 Cadastral brass cap, firmly set with steel fence post alongside and burned stumps of BTs.

We go 75 ft. South for WITNESS CORNER and Reset brass cap & steel fence post alongside, now marked:

W.C. 75 ft. N to cor.

T20S R8W	S 34	S 35
----------	------	------

T21S R8W	S 3	S 2
----------	-----	-----

New BTs- 54" D.Fir stump, N.30°E., 7.5 ft. mkd. W.C. T20S R8W S35 CS BT.

48" D.Fir stump, S.47°E., 28.4 ft. mkd. W.C. T21S R8W S2 CS BT.

60" D.Fir stump, N.51°W., 27.6 ft. mkd. W.C. T20S R8W S34 CS BT.

The old position of this corner was near centerline of new logging access road to be constructed. This witness corner lies on SW. slope of ridge SW. of proposed road junction.

(Cont. Next Page)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew
Oct. 31, 1967 - C.S. File 54/67 - C.S. File

Move Witness Corner set in July 1967 from its location 75 ft.
South of true corner, 20 ft. N., or 55 ft. S. of true corner
location.

New BTs- 12" Hemlock stump N.38°W., 6.7 ft. mkd. W.C. T20S
R8W S34 CS BT.

18" Hemlock stump N.12°E., 10.5 ft. mkd. W.C. T20S
R8W S35 CS BT.

14" Hemlock stump S.88°E., 6.4 ft. mkd. W.C. T21S
R8W S2 CS BT.

Nothing available in section 3.

RESET steel fence post alongside brass cap.

This Witness Corner lies in "Y" of new logging roads on top
of ridge. We obliterate scribe on BT stumps mkd. in July
1967.

BLM dependent resurvey by Edith M Forkner, Cadastral
Surveyor, under Group #2780, surveyed March/Aug. 2015 - (DCSO
records Vol. 58 Page(s) 23443-5 & Plat T20-8 2016-1)

The cor. of secs. 2, 3, 34, & 35, on the S. bdy. of the Tp.,
as determined at record bearing and from the remains of the
original bearing tree

A burned decayed fir stump, 55" dia.. bears S.35°E., 19.1
ft., no marks visible.

and the witness cor. established by the Douglas County
Surveyor's Office in July, 1967, reset by the Douglas County
Surveyor's Office in October, 1967; monumented with an iron
post, 2" dia., firmly set, projecting 8" above ground, bears
South, 55.00 ft., with a brass cap mkd. WC 55 FT T20S R8W S34
S35 S3 S2 N TO COR T21S 1950, and a steel fence post
alongside. This monument now functions as a reference
monument; remark the brass cap as RM T21S R8W S2 55.0 FT TO
COR 2015 1950 and an arrow pointing to the cor., from which
the remains of the bearing trees mkd. by the Douglas County
Surveyor's Office in October, 1967

Hemlock remains, size indeterminate, bears N.12°E., 10.5
ft., no marks visible.

A decayed hemlock stump, size indeterminate, bears
S.88°E., 6.4 ft., no marks visible.

A decayed hemlock stump, size indeterminate, bears
N.38°W., 6.7 ft., no marks visible.

At the corner point Drive a finned aluminum rod, 30" long, 3/4"
dia., 28" in the ground, with an aluminum cap mkd:

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec Cor for 2 & 3; 34 & 35, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 20S R8W
S 34|S 35
S 3|S 2
T 21 S
2015

from which new bearing trees
A fir, 13" dia., bears N.41½°E., 70.0 ft., mkd. T20S R8W S35 BT.
A fir, 16" dia., bears S.67°E., 30.7 ft., mkd. T21S R8W S2 BT.
A fir, 18" dia., bears S.68°W., 50.0 ft., mkd. T21S R8W S3 BT.
A fir, 23" dia., bears N.67°W., 75.4 ft., mkd. T20S R8W S34 BT.

Corner is located in the loose dirt of a cut bank and 20 ft. S. of a graveled road, 10 ft. wide, bears N.70°E. and N.75°W.

Fd. Ok by DCSO SJF & JL 4/23/2020 C.S. File 67/46-51
Lat: 43.776871266 Long: -123.621257369