

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 26

Alias	Description

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22071)

Point for the center ¼ sec. cor. of sec. 26, at intersection with the E & W center line.
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T21S R8W
C ¼ S26
2007

from which
A hemlock, 15" dia. bears S.78°E., 10.4 ft. mkd. C¼ S26 BT
A fir, 13" dia., bears S.67½°W., 40.7 ft. mkd. C1/4 S26 BT
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.
Deposit a magnet in a white plastic case at the base of the stainless steel post.
Corner is located on a steep NE. slope.

Ronald L. Rice, Ward NW - Dec. 2011 - C.S. File 65/72-48

-
- Found - 3¼" BLM brass cap (properly mkd) dated 2007 with the following accessories:
 - 15"x8' Hemlock stump bears S.78°E., 10.4' with scribing visible and "Mag Nail" @ side center
 - 13"x8' D.Fir stump bears S.67½°W., 40.7' with scribing visible and "Mag Nail" @ side center
 - New - Corner was referenced and removed to protect it from logging, then reset after logging based on my references. Magnet set at the base of monument in 2007 remained in place. Corner is located in recent clear cut with limited accessories.
 - Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags. Corner falls in recent clear cut.
Compass Declination 16° east