

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 850)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on N face from which:

Alder, 7" dia., bears N.29°E., 16 lks., mkd: 1/4 S BT.

Alder, 6" dia., bears N.67°W., 42 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12573)

Point for the 1/4 sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 27" in the ground with brass cap marked:

1/4 S 23
 S 26
 1952

from which

A Fir, 21" dia., bears N.84 1/4°W., 27 lks., mkd: 1/4 S23 BT.

A Fir, 65" dia., bears S.12°45'W., 130 lks., mkd: 1/4 S26 BT

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22072)

The 1/4 sec. cor. of secs. 23 & 26, monumented with an iron post, 1" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which new bearing trees

A fir, 17" dia., bears S.4 3/4°E., 27.0 ft., mkd. 1/4 S26 BT.

A fir, 16" dia., bears N.36°W., 37.0 ft., mkd. 1/4 S23 BT.

Each new bearing tree has a 2 1/2" x 1/4" magnetic nail (Mag Nail) driven at the base right side-center.