

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 853)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on N face from which:

Fir, 5" dia., bears N.10°E., 27 lks., mkd: 1/4 S BT.

Fir, 5" dia., bears S.73°W., 42 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12579-80)

Point for the 1/4 sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

1/4 S 11
S 14
1954

from which

A Hemlock, 21" dia., bears N.74°E., 37 lks., mkd: 1/4 S11 BT

A Hemlock, 15" dia., bears S.34°E., 47 lks., mkd: 1/4 S14 BT

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Gary Smithers - For: Roseburg Resources - 8/2006 - M151-44

Found - 1954 BLM brass cap DCSO recs. Vol 30 page 12579-80
31" hemlock N.74°E., 24.1 ft. with healed face

34" hemlock stump S.34°E., 40.1 ft. with healed face

New BTs- 11" Alder S.60°W., 9.7 ft. to spike side center bark
scribe T21R8 1/4 S14 BT

11" cedar N.67°W., 25.0 ft. to spike side center
scribe T21R8 1/4 S11 BT

BLM Corrective Dependent resurvey by Aaron M. Graham, Cadastral Surveyor, under Group #2150, surveyed Sept. 2006/April 2007 - (DCSO rec. Vol. 56 Page 22107 & BLM Plat T21-8 2010-1)

Point for the 1/4 sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the original corner.
Continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T21S R8W
¼ $\frac{S\ 11}{S\ 14}$
2007

from which

A fir, 8" dia., bears S.24°W., 17.8 ft., mkd. ¼ S14 BT

A fir, 8" dia., bears N.81¼°W., 33.7 ft., mkd. ¼ S11 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this cor., a point erroneously established as the ¼ cor. of secs. 11 and 14 by Lytle, et al., in 1952-54, and rehabilitated by Smither, in 2006, and was not accepted in this survey due to improper procedure, bears N.88°27'33"E., 52.98 ft.; monumented with an iron post, 1" dia., firmly set, projecting 10" above ground, with brass cap mkd. S11 ¼ S14 1954. Remove these marks and remark the cap to read AM 53 FT TO COR 2007 with an arrow pointing to the corner.