

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 855)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 S on N face from which:

Fir, 8" dia., bears N.60°E., 4 lks., mkd: 1/4 S BT.

Hemlock, 6" dia., bears S.75°W., 17 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12583-4)

The 1/4 sec. cor. of secs. 2 & 11 determined at the record bearing & distance from the orig. BT, as follows:

A Fir, 30" dia., bears N.60°E., 4 lks., plainly blazed & healed; I uncover portion of blaze & expose scribe mark S at proper age.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 24" in the ground to solid rock, and in a small mound of stone to top, with brass cap marked:

1/4 S 2

 S 11

 1954

from which new BTs:

A Hemlock, 10" dia., bears S.77 1/2°E., 6 lks., mkd: 1/4 S11 BT

A Fir, 25" dia., bears **N.48 1/2°W.***, 45 lks., mkd: 1/4 S2 BT.

BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1)

The 1/4 sec. cor. of secs. 2 & 11, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly marked) from which the remaining OBT

A burned Fir, 30" dia., bears N.60°E., 4 lks., no marks remaining on burned blaze.

and BTs mkd. in 1954

A burned Hemlock, 15" dia., bears S.77 1/2°E., 6 lks., no marks remaining on burned blaze.

A burned Fir, 30" dia., **N.48 1/2°W.***, 45 lks., with healed blaze.

Set a 6 ft. fence post alongside the iron post.

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Joel E. Robb, Cadastral Surveyor, under Group # 1171, surveyed Aug./Sept. 1983 - (DCSO records Vol. 46 Page(s) 17800-1)

Beginning at the ¼ sec. cor. of secs. 2 & 11, monumented with an iron post, 1" dia., firmly set, projecting 12" above ground, alongside of which is a steel fence post, loosely set, projecting 5 ft. above ground, with properly marked brass cap,

from which the remaining OBT

A Fir, 40" dia., bears N.60°E., 4 lks., with opened blaze, no marks visible.

and a BT mkd. by Lytle, Norseth, Tillman, Bicknell, Gawron, & Thielsen

A Fir, 33" dia., bears **N.48½°E.***, 45 lks., with healed blaze.

and new BT:

A Maple, 21" dia., bears S.66¼°E., 118 lks., mkd: ¼ S11 BT

* The 1954 & 1967 BLM notes say NW and the 1983 say NE