

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 571100

PRIMARY CORNER DESCRIPTION C C for secs. 1 & 2 only, T22-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. H. Byars, under Contract #376 dated Jan. 22, 1881 (DCSO records Vol. 4 Page(s) 1597)

-----  
Intersect North bdy. of Tp. 825 lks. West of cor. to Secs. 35 and 36.

Set Fir post at point of intersection for sec. cor. to secs. 1 & 2, from which

A Fir 20" dia., bears S.60°E., 35 lks. dist.

A Fir 16" dia., bears S.20°W., 43 lks. dist.

GLO resurvey by M. Lytle; P. Norseth; T. Tillman; R. Bicknell; J. Gawron & H. Thielsen, Cadastral Engineers, under Group #304, surveyed Aug. 1952-Oct. 1954 (DCSO records Vol. 30 Page(s) 12545)

-----  
The closing cor. of secs. 1 and 2, bears South, 9 lks. dist. determined from the remaining original bearing tree, as follows:

A Fir 30" dia., bears S.20°W., 43 lks. dist. with scribe marks visible on nearly healed blaze.

At point on line

Set an iron post 3 ft. long, 2" dia., 27" in the ground with brass cap mkd:

T 21	S	R	8	W
	S	35		
	S	2	S	1
T 22	S	R	8	W
	C	C		
	1952			

from which

A Fir 7" dia., bears S.77¼°E., 43 lks. dist., mkd. T22S R8W S1 CC BT. (New bearing tree).

A Fir 30" dia., bears S.16½°W., 52 lks. dist. with scribe marks visible on nearly healed blaze. (old bearing tree).

A Fir 35" dia., bears S.74°W., 71 lks. dist. mkd. T22S R8W S22 CC BT. (New bearing tree).

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone, crew - Sept. 1963 - C.S. File 52/14-24

-----  
Found - Brass cap set in 1952.

All BTs called for in govt. notes, 1952, found but all are uprooted and down. (fairly recent).

New BTs -11" D.Fir S.83°W., 63.7 ft. "T22S R8W CC S2 CS BT."  
22" Madrone N.36°W., 94.0 ft. mkd. CC S1 S2 CS BT.

No trees available in section 1.

Bottom of blaze on Madrone 4 ft. above ground.

(Cont. Next Page)

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 571100

PRIMARY CORNER DESCRIPTION C.C. for secs. 1 and 2 only, T22-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd. OK, March 1983, Les Roberts, M 94-6

BLM remonumentation by Aaron M Graham, Cadastral Surveyor and Michael Jones Surveying Technician under Group #2199 surveyed April 2008/April 2009 - (DCSO rec. Vol. 56 Pgs 21940-1)

-----  
The closing cor. of secs. 1 and 2, on the N. bdy. of the Tp., established by Lytle et.al., in 1952-54; monumented with an iron post, 2" dia., firmly set, projecting 11" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Lytle, et al., in 1952-54

A roothole, bears S.77 $\frac{1}{4}$ °E., 28.4 ft., onside of which is a down decayed fir, 5" dia., with scribe marks CC T22S R8 visible on open blaze and reverse scribes on loose piece.

A roothole, bears S.74°W., 46.9 ft., onside of which is a down fir stump, 30" dia., no marks visible.  
and the bearing trees mkd. by Godfrey in 1962-63

A fir, 18" dia., bears S.84°W., 63.4 ft., with a healed blaze.

A madrone, decayed in center but still alive, 20" dia., bears N.34 $\frac{1}{4}$ °W., 92.3 ft., no marks visible.  
and a bearing tree mkd. by Forkner in 2007

A fir, 16" dia., bears S.85 $\frac{1}{4}$ °E., 29.0 ft., with scribe marks T22S R8W S1 CC BT visible on partially healed blaze.

The original closing cor. of secs. 1 and 2, determined at record bearing and distance from the remains of an original bearing tree (S.0°55'39"E. 5.94 ft. from 1952 CC)

A decayed fir stump, 42" dia., bears S.20°W., 28.4 ft. no marks visible on open blaze and axe marks in a diamond on the east side.

At the corner point

Set a steel reinforcing rod, 36" long, 5/8" dia., 36" in the ground.

No further monumentation deemed necessary.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22051-2)

-----  
The closing cor. of secs. 1 & 2, on the N. bdy. of T22S R8W monumented with an iron post, 2" dia., firmly set, projecting 11 ins. above ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 571100

PRIMARY CORNER DESCRIPTION C.C. for secs. 1 & 2 only, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which remains of the BTs mkd. by Lytle, et al in 1952-54  
A roothole bears S.77¼°E., 28.4 ft., alongside of which is  
a down decayed fir, 5" dia., with scribe marks CC T22S  
R8 visible on open blaze and reverse scribes on loose  
piece.

A roothole bears S.74°W., 46.9 ft., with a down fir stump,  
30" dia., alongside, no marks visible.  
and BTs mkd. by Godfrey, in 1963

A fir, 18" dia., bears S.84°W., 63.4 ft., with a healed  
blaze.

A madrone, rotted in center but still alive, 20" dia.,  
bears N.34¼°W., 92.3 ft., no marks visible.  
and a new bearing tree

A fir, 16" dia., bears S.85¼°E., 29.0 ft., mkd. T22S R8W  
S1 CC BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag  
Nail) driven at the base right side-center.

An iron rod with International Paper Co. property sign is  
alongside the cor.

Corner is located on a W. slope in the middle of a bench, 100  
ft. wide.

From this corner, the point for the original closing cor. of  
secs. 1 and 2, bears South, 5.9, not monumented, determined  
at record bearing and distance from the remains of an  
original bearing tree

A decayed fir stump, 20" dia., bears S.20½°W., 28.4 ft.,  
with no marks visible on open blaze and axe marks in a  
diamond on the east side.