

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 838)

Fir, 50" dia., for 1/4 sec. corner marked 1/4 S on W faces from which:

Hemlock, 18" dia., bears West, 33 lks., mkd: 1/4 S BT.

Hemlock, 24" dia., bears East, 50 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12556)

Point for 1/4 sec. cor. of secs. 35 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap marked:

1/4
S 35|S 36
1952

from which

A Fir, 35" dia., bears S.33°E., 30 lks., mkd: 1/4 S36 BT.

A Fir, 62" dia., bears S.12 1/4°W., 23 lks., mkd: 1/4 S35 BT.