

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 838)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 25, 26, 35 & 36, marked T21S, S 25 on NE, R8W, S 36 on SE, S 35 on SW, S 26 on NW face with one notch on E & S edge from which:

- Fir, 18" dia. bears N.76°W., 36 lks., mkd: T21S R8W S26 BT
- Fir, 12" dia. bears S.14°W., 33 lks., mkd: T21S R8W S35 BT
- Fir, 6" dia., bears S.70°E., 40 lks., mkd: T21S R8W S36 BT
- Fir, 18" dia. bears N.70°E., 61 lks., mkd: T21S R8W S25 BT

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12557)

The cor. of secs. 25, 26, 35 & 36, determined at the record bearing & dist. from each of the remaining orig. BTs, as follows:

- A Fir snag, 22" dia., bears N.70°E., 61 lks., showing a burned resinous blaze facing SW.
- A Fir stump, 12" dia., bears S.72½°E., 40 lks., with old scribe marks still visible. (Rec. bearing S.70°E.)
- A stump hole, bears S.14°W., 33 lks.
- A Fir, 37" dia., bears N.77½°W., 36 lks., showing old axe marks on scarred SE face. (Rec. bearing, N.76°W.)

At the corner point

Set an iron post, 3 ft. long, 1" dia., 274" in the ground, with brass cap marked:

T21S	R8W
<u>S 26</u>	<u>S 25</u>
S 35	S 36
1952	

from which

- A Fir, 28" dia., bears N.7¼°E., 124 lks., mkd: T21S R8W S25 BT.
- A Fir, 23" dia., bears S.18°E., 76 lks., mkd: T21S R8W S36 BT.
- A Fir, 45" dia., bears S.26½°W., 42 lks., mkd: T21S R8W S35 BT.
- A Fir, 20" dia., bears N.73½°W., 94 lks., mkd: T21S R8W S26 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 25, 26, 35, & 36

Alias	Description

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22055-6)

The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia., firmly set, projecting 9" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree
A decayed fir stump, 36" dia., bears N.77½°W., 23.8 ft., no marks visible.

and the remains of the BTs mkd. by Lytle, et al., in 1952-54
A decayed fir stump, 30" dia., bears N.7¼°E., 81.8 ft., no marks visible.

A decayed fir stump, 23" dia., bears S.18°E., 50.2 ft., no marks visible.

A decayed fir stump, 42" dia., bears S.26½°W., 27.7 ft., no marks visible.

A decayed fir stump, size indeterminate, bears N.73½°W., 62.0 ft., no marks visible.

and bearing trees mkd. by person(s) unknown

A fir, 12" dia., bears S.28°E., 20.9 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

A fir, 14" dia., bears S.37¼°W., 16.7 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

A fir, 15" dia., bears S.86½°W., 17.2 ft., with a healed blaze with a nail and washer in face, and a nail on the right side center.

and new bearing trees

A fir, 10" dia., bears N.24½°E., 53.3 ft., mkd. T21S R8W S25 BT.

A fir, 19" dia. bears N.6°W., 85.3 ft mkd. T21S R8W S26 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

A steel fence post is alongside the cor. and a fir, 2 ft. dia., bears N.20°W., 20 ft., with a BLM location tag.

Douglas Co. Surveyors Office - Crew: Stephen J Flauser & Jeff Lorsung - 10/12/2020 - C.S. File 67/46-45

3 BTs by person(s) unknown fd as described.

2007 New (10") BT now 12"x10" sawn stub

2007 New (19") BT now 22"x7 ft sawn stmp

Lat: 43.707494733 Long: -123.604220884