

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 840)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 23, 24, 25, & 26, marked T21S, S 24 on NE, R8W, S 25 on SE, S 26 on NW face with one notch on E edge & 2 on S edges from which:

- Fir, 36" dia., bears N.8°W., 26 lks., mkd: T21S R8W S23 BT
- Fir, 30" dia. bears N.10°E., 53 lks., mkd: T21S R8W S24 BT
- Dogwood, 6" dia. bears S.2°W. 42 lks. mkd: T21S R8W S26 BT
- Dogwood, 7" dia., bears S.16°E., 47 lks., mkd: T21S R8W S25 BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO recs. Vol 30 Page 12559)

Point for the cor. of secs. 23, 24, 25, & 26, determined from the former positions of the orig. NE & NW BTs, both of which have fallen & slid some 3 chs. northeastward, and which were identified by the orig. scribe marks:

- A stump hole, bears N.10°E., 53 lks.
- A stump hole, bears N.8°W., 26 lks.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 26" in the ground, with brass cap marked:

T21S R8W
<u>S 23 S 24</u>
S 26 S 25
1952

from which

- A Fir, 25" dia., bears N.40¼°E., 172 lks., mkd: T21S R8W S24 BT.
- A Fir, 32" dia., bears S.49½°E., 95 lks., mkd: T21S R8W S25 BT.
- A Fir, 53" dia., bears S.35½°W., 93 lks., mkd: T21S R8W S26 BT.
- A Fir, 42" dia., bears N.31¼°W., 224 lks., mkd: T21S R8W S23 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22058-9)

The cor. of secs. 23, 24, 25, & 26, monumented with an iron post, 2" dia., firmly set, projecting 5 ins. above ground, with brass cap (properly) mkd.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Cor. Secs. 23, 24, 25, & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the BTs mkd. by Lytle, et al., in 1952-54

A fir stump, 35" dia., bears N.44°E., 111.0 ft., no marks visible. (Record, N.40¼°E., 113.5 ft.)

A fir stump, 30" dia., bears S.48°E., 62.7 ft., no marks visible. (Record, S.49½°E.)

A fir stump, 43" dia., bears S.35½°W., 61.4 ft., with scribe marks S 6 BT and other illegible scribe marks visible on partially healed blaze.

A fir stump, 33" dia., bears N.28½°W., 147.8 ft., with illegible scribe marks visible on detached partially healed blaze. (Record, N.31¼°W.)

and new bearing trees

A fir, 12" dia. bears N.68°E., 6.4 ft mkd. T21S R8W S24 BT

A fir, 11" dia. bears S.¼°E., 8.8 ft. mkd. T21S R8W S25 BT

A fir, 11" dia., bears S.14¼°W., 15.2 ft., mkd. T21S R8W S26 BT.

A fir, 11" dia., bears N.85¾°W., 29.7 ft., mkd. T21S R8W S23 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.