

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 842)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 13, 14, 23, & 24, marked T21S, S 13 on NE, R8W, S 24 on SE, S 23 on SW, S 14 on NW face with one notch on E and 3 on S edge from which:

- Fir, 40" dia., bears N.30°W., 27 lks., mkd: T21S R8W S14 BT.
- Fir, 60" dia., bears S.75°W., 27 lks., mkd: T21S R8W S23 BT.
- Hemlock, 10" dia., bears S.45°E., 30 lks., mkd: T21S R8W S24 BT.
- Hemlock, 8" dia., bears N.25°E., 60 lks., mkd: T21S R8W S13 BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12561)

The cor. of secs. 13, 14, 23, & 24, determined from the OBTs as follow:

- A hemlock snag, 18" dia., bears N.25°E., 60 lks., with partial scribe marks visible.
- A dead & fallen hemlock, 12" dia., bears S.45°E., 30 lks., with blazed healed.
- A Fir, 60" dia., bears S.75°W., 27 lks., with no marks visible on burned blaze.
- A Fir, 55" dia., N.30°W., 27 lks., with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground with brass cap marked:

T21S	R8W
<u>S 14</u>	<u>S 13</u>
S 23	S 24
1954	

from which

- A Cedar, 25" dia., bears N.88°E., 58 lks., mkd: T21S R8W S13 BT.
- A Hemlock, 26" dia., bears S.34°45'E., 101 lks., mkd: T21S R8W S24 BT.
- A Fir, 35" dia., bears S.42°W., 73 lks., mkd: T21S R8W S23 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April/May 1968 - C.S. File 54/67

-
- Found - 1954 GLO brass cap, properly mkd.
Orig. 55" now 60" Fir, almost dead, N.30°W., 17.8 ft., show good scar.
Orig. 60" Fir stump, burned S.75°W., 17.8 ft., no scribe found.
All other BTs destroyed by logging.
 - New BTs- 26" Fir stump S.33°E., 34.7 ft., mkd: T21S R8W S24 CS BT.
48" Fir stump S.26°W., 35.3 ft., mkd: T21S R8W S23 CS BT.
 - Note - Set 6 ft. steel fence post alongside brass cap.
This corner lies approx. 450 ft. N. of Paradise Creek access road in reproduction of D.Fir & Hemlock.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20739)

-
- The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2" diam, firmly set, projecting 4" above the ground, with brass cap (properly)mkd.
from which the remains of the original bearing trees
- A root hole, bears S.45°E., 19.8 ft.
 - A fir stump, 41" dia., bears S.75°W., 17.8 ft., with no marks visible.
 - A fir stump, size indeterminate, bears N.30°W., 17.8 ft., with scribe marks S1 visible on rotted blaze.
- and the remains of a BT mkd. by Lytle, et. all
- A hemlock stump, 24" dia., bears S.34¾°E., 66.7 ft., no marks visible.
- and new bearing trees
- A hemlock, 17" dia., bears N.33°E., 35.5 ft., mkd. T21S R8W S13 BT.
 - A fir, 14" dia., bears S.61½°E., 20.9 ft., mkd. T21S R8W S24 BT.
 - A cedar, 6" dia., bears S.58½°W., 31.0 ft., mkd. T21S R8W S23 BT.
 - A fir, 11" dia., bears N.54°W., 9.3 ft., mkd. T21S R8W S14 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias	Description

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22061-2)

The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A burned decayed fir stump, 41" dia., bears S.75°W., 19.5 ft., no marks visible. (Record, 17.8 ft.)

A decayed fir stump, size indeterminate, bears N.3°W., 20.2 ft., with scribe marks 21S R8 visible on detached blaze. (Record, 17.8 ft.)

and the remains of a bearing tree mkd. by Lytle, et al., in 1952-54

A decayed hemlock stump, 14" dia., bears S.33½°E., 66.7 ft., no marks visible. (Record, S.34¾°E.)

and the remains of the BTs mkd. by Graham in 1999-2000

A hemlock, 19" dia., bears N.33°E., 35.5 ft., with scribe marks 21S R8W S13 BT visible on partially healed blaze.

A fir snag, 15" dia., bears S.61½°E., 20.9 ft., with illegible scribe marks visible on partially healed blaze.

A cedar, 10" dia., bears S.58½°W., 31.0 ft., with scribe marks T21S R8W S23 BT visible on partially healed blaze

A fir, 11" dia., bears N.54°W., 9.3 ft., with a healed blaze.

and a new bearing tree

A fir, 19" dia., bears S.40¼°E., 47.9 ft., mkd. T21S R8W S24 BT.

A red metal fence post is alongside the cor.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.