TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 843)

Fir, 14" dia., for ¼ sec. cor. marked stone ¼ S on W face, from which:
Fir, 20" dia., bears N.80°E., 27 lks., mkd: ¼ S BT.
Fir, 6" dia., bears N.70°W., 20 lks., mkd: ¼ S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12563)

Point for the ¼ sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked: ¼
S 14 | S 13
1954
from which
A Fir, 50" dia., bears S.89°E., 74 lks., mkd: ¼ S13 BT.
A Fir, 40" dia., bears S.68°45'W., 310 lks., mkd: ¼ S14 BT

David Edwards - Brant Miller & Eric Sprinkle, Crew - 4/30/2014 - C.S. File 65/82-33

Found - 1954 BLM brass cap.
Fir stump S.68°45'W., 204.6' other 1954 BT gone.
New - No trees large enough to scribe in Section 14.
An 8" dia. Fir scribed. "T21S R8W S13 BT" bears N.80°E., 9.1 ft.
A 15" dia. Fir scribed. T21S R8W S13 BT" bears S.24°E., 14.1 ft.
A 6 ft steel post is set 2 ft.
Compass decl. 15½°E.