

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 843-4)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 11, 12, 13, & 14, marked T21S, S 12 on NE, R8W, S 13 on SE, S 14 on SW, S 11 on NW face with one notch on E & 4 on S edge from which:

- Maple, 12" dia., bears N.48°E., 30 lks., mkd: T21S R8W S 12 BT.
- Maple, 5" dia., bears S.8°W., 36 lks., mkd: T21S R8W S14 BT.
- Fir, 90" dia., bears S.75°E., 37 lks., mkd: T21S R8W S13 BT.
- Fir, 80" dia., bears N.75°W., 33 lks., mkd: T21S R8W S11 BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12563-4)

The cor. of secs. 11, 12, 13, & 14, determined from the remaining OBTs as follows:

- A Maple, 20" dia., bears N.48°E., 30 lks., with blaze healed.
- A Maple, 16" dia., bears S.3½°W., 52 lks., with blazed healed. (Rec. bearing S.8°W., 36 lks.)
- A Fir snag, 80" dia., bears N.75°W., 33 lks., with blazed healed.

Set an iron post, 3 ft. long, 2" dia., 30" in the ground, with brass cap marked:

	T21S	R8W
	<u>S 11</u>	<u>S 12</u>
	S 14	S 13
	1954	

from which new BTs,

- A Hemlock, 12" dia., bears N.22½°E., 81 lks., mkd: T21S R8W S12 BT.
- A Hemlock, 22" dia., bears S.37°45'E., 112 lks., mkd: T21S R8W S13 BT.
- A Fir, 20" dia., bears S.14°W., 87 lks., mkd: T21S R8W S14 BT.
- A Cedar, 50" dia., bears N.29°W., 95 lks., mkd: T21S R8W S11 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Les Roberts - For: International Paper Co. - June 26, 1981 - M 88-22

Found - Brass cap (GLO)
12" Maple bears South, 35.0 ft. (no scar) 1883 BT.
20" Maple bears N.48°E., 20.4 ft. (scar visible) 1883 BT.
68" Fir stump bears N.76½°W., 22.2 ft. (scar vis.) 1883 BT.
24" Fir bears S.13°W. 56.7 ft (scar visible) 1954 BT
29" Hemlock bears S.38°E., 75.0 ft. (scribe vis.) 1954 BT.
46" Cedar bears N.28½°W., 62.0 ft. (scribe vis.) 1954 BT.

FD. OK Gary Smithers - Aug. 2006 - M151-44

BLM Corrective Dependent resurvey by Aaron Graham, Cadastral Surveyor, under Group #2150, surveyed Sept. 2006/April 2007 - (DCSO rec. Vol. 56 Page 22107 and BLM Plat T21-8 2010-1)

The cor. of secs. 11, 12, 13, & 14, perpetuated by Lytle et. al., in 1952-54; monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.
from which the remains of the original BTs
A maple, 26" dia. bears N.48°E., 19.8 ft., with a partially healed hole through the base.
A maple, 16" dia., bears S.1/4°W., 34.3 ft., with a healed blaze. (Record, S.3½°W.)
A fir stump, 57" dia., bears N.75°W., 21.8 ft., with axe marks X at breast height.
and the remains of the BTs mkd. by Lytle, et al.
A hemlock snag, 30" dia., bears S.38¾°E., 73.9 ft., with healed blaze. (Record, S.37¾°E.)
A fir, 35" dia., bears S.14°W., 57.4 ft., with a healed blaze.
A cedar, 53" dia bears N.29°W. 62.7 ft with a healed blaze
An aluminum fence post is alongside the cor.
Corner is located 5 ft. N. of a rootwad.

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2720, surveyed Aug./Oct. 2013 - (DCSO records Vol. 58 Page(s) 23118-9)

The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.

from which the remains of the original bearing trees

A maple, 28" dia., bears N.48°E., 19.8 ft., with a healed blaze.

A maple, 16" dia., bears S.1/4°W., 34.3 ft., with a healed blaze. (Record, S.3 1/2°W.)

A decayed fir stump, 54" dia., bears N.75°W., 21.8 ft., with no marks visible.

and the remains of the BTs mkd. by Lytle, et al, in 1952-54

A decayed hemlock snag, 31" dia., bears S.38 3/4°E., 73.9 ft., with a healed blaze. (Record, S.37 3/4°E.)

A fir, 36" dia., bears S.14°W., 57.4 ft., with a healed blaze.

A cedar, 54" dia., bears N.29°W., 62.7 ft., with a healed blaze.

Alongside is an aluminum fence post.

From the corner

N.1°12'14"E., 180 ft., creek, 3 ft. wide, course N.30°W.

N.89°18'44"E., 100 ft., creek, 12 ft. wide, course N.30°W.
NAD 1983 (2011)

Latitude: 43°44'53.51"N. Longitude: 123°36'13.05"W.