

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 845-6)

Set post 6" dia., 4 ft. long with marked stone 12" in ground for corner to secs. 1, 2, 11, & 12, marked T21S, S 1 on NE, R8W, S 12 on SE, S 11 on SW, S 2 on NW face with one notch on E & 5 on S edge from which:

- Fir, 15" dia., bears N.80°E., 41 lks., mkd: T21S R8W S1 BT.
- Fir, 7" dia., bears S.82°E., 49 lks., mkd: T21S R8W S12 BT.
- Fir, 15" dia., bears S.71°W., 95 lks., mkd: T21S R8W S11 BT.
- Fir, 10" dia., bears N.16°W., 100 lks., mkd: T21S R8W S2 BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12565-6)

The cor. of secs. 1, 2, 11, & 12, determined from the remaining OBT, as follows:

A Fir & Cedar, grown together, 50" dia., bears S.71°W., 95 lks., with blaze nearly healed. I open & uncover scribe marks S11 BT T21S R under 71 years overgrowth. (Wright calls for a Fir, but the marks are actually in the cedar wood of the composite tree.)

Set an iron post, 3 ft. long, 2" dia., 28" in the ground and in a small mound of stone to top, with brass cap marked:

| | |
|------|------|
| T21S | R8W |
| S 2 | S 1 |
| S 11 | S 12 |
| 1954 | |

from which

- A Fir, 23" dia., bears N.44°E., 64 lks., mkd: T21S R8W S1 BT.
- A Hemlock, 23" dia., bears S.8¼°E., 36 lks., mkd: T21S R8W S12 BT.
- A Hemlock, 12" dia., bears S.47½°W., 16 lks., mkd: T21S R8W S11 BT.
- A Fir, 11" dia., bears N.7°W., 8 lks., mkd: T21S R8W S2 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

Fd. Ok on BLM remonumentation of certain orig. corner points by Wm. W. Glenn & James E. Jelley, Cadastral Surveyors, under group #s 350 & 635, surveyed April/May 1967 - (DCSO records C.S. File 65/27-1) ** also set a 6 ft. steel fence post alongside the iron post.**

Les Roberts - For: International Paper Co. - June 26, 1981 - M 88-22

Found - Brass cap (GLO)
26" Cedar bears S.72°W., 61.4 ft. (scribe vis.) 1883 BT.
11" Fir bears N.1°E., 5.0 ft. (scar vis.) 1954 BT
22" Hemlock bears S.9°E., 23.4 ft. (scar vis.) 1954 BT.
30" Fir bears N.44°E., 42.5 ft. (scar vis.) 1954 BT.

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2720, surveyed Aug./Oct. 2013 - (DCSO records Vol. 58 Page(s) 23120-1)

The cor. of secs. 1, 2, 11, & 12, monumented with an iron post, 2" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd.
from which the remains of an original bearing tree
A fir and cedar stump, 61" dia., bears S.71°W., 62.7 ft., with a healed blaze.
and the remains of the BTs mkd. by Lytle, et al, in 1952-54
A fir stump, 31" dia., bears N.44°E., 42.2 ft., with no marks visible and an aluminum cap.
A decayed hemlock stump, size indeterminate, bears S.8¼°E., 23.8 ft., with a healed blaze.
A decayed fir stump, 14" dia., bears N.7°W., 5.3 ft., with a healed blaze.
and new bearing trees
A fir, 8" dia., bears N.44½°E., 21.8 ft., mkd. T21S R8W S1 BT.
A fir, 11" dia., bears S.52¼°E., 26.8 ft., mkd. T21S R8W S12 BT.
A fir, 7" dia., bears S.68½°W., 12.6 ft., mkd. T21S R8W S11 BT.
A fir, 10" dia., bears N.41¼°W., 5.2 ft., mkd. T21S R8W S2 BT.
Alongside is a steel fence post.