

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 839)

Maple, 20" dia. for 1/4 sec. cor. mkd 1/4 S on N face from which:
Maple, 18" dia., bears N.25°E., 10 lks., mkd: 1/4 S BT.
Chinquapin, 12" dia., bears S.12°W., 47 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J Lytle, Palmer Norseth, Thomas A Tillman, Raymond M Bicknell, Joseph S Gawron & Hans W Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Pg 12558)

Point for 1/4 sec. cor. of secs. 25 & 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 12" long, 1" dia., 10" in drill hole in sandstone bedrock swelled into hole by a metal wedge in the split lower end, with brass cap marked:
$$\frac{1}{4} \frac{S \ 25}{S \ 36}$$

1952
from which
A W. Fir, 35" dia., bears S.64°E., 74 lks., mkd: 1/4 S36 BT.
A Fir, 57" dia., bears N.66°W., 52 lks., mkd: 1/4 S25 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April 1968 - C.S. File 54/67

Found - No trace of 1952 GL0 brass cap, apparently destroyed by road construction.
35" W. Fir, now stump, S.64°E., 48.8 ft., scribe visible on burned blaze. Rescribed "1/4 S36 CS BT"
Set - Brass cap at cor. mkd: COUNTY SURVEYORS T21S R8W
OFFICE 1/4 S 25
1968 S 36
No trees close. Steel fence post with yellow line tag bears West 44.0 ft.
Corner lies on East side of road at foot of fill & west of edge of creek, course S.30°W.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22054-5)

The 1/4 sec. cor. of secs. 25 & 36, perpetuated by Douglas Deputy County Surveyor's Office, in 1968, monumented with an iron post, 1 1/2" dia., firmly set, projecting 30" above ground, in a mound of stone, 2 ft. base, 24" high, with brass cap (properly) mkd. continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 25 & 36

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

from which the remains of a BT mkd by Lytle, et al in 1952-54
A decayed W.Fir stump, size indeterminate, bears S.64°E.
48.8 ft. no marks visible.
and bearing trees mkd. by person(s) unknown
An alder, 11" dia., bears N.20¾°E., 19.3 ft., no marks
visible.
An alder, 12" dia., bears S.11½°W., 9.3 ft., with
illegible scribe marks visible on bark.
Drive a red Carsonite post alongside the cor.
Corner is located at the bottom of the fill bank for Paradise
Creek Road.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 11/21/2024 - C.S. File 67/59-14

Found - DCS0 brass cap (properly mkd) flush with ground.
10"x8 ft. rotted alder snag N.20¾°E., 19.3 ft.
14" Alder S.11½°W., 9.3 ft. with illegible bark
scribes.
New - A 14" alder N.20°E., 8.7 ft., bark scribed ¼ S25 BT.
Note - Area burnt 9/2020
Compass decl. 14¾°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 318758.765 E 95188.412