

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 843)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for 1/4 sec. cor. marked 1/4 on N face from which:

- Cedar, 18" dia., bears S.18°W., 42 lks., mkd: 1/4 S BT.
- Fir, 12" dia., bears N.50°E., 14 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952 thru Oct. 1954 - (DCSO recs. Vol. 30 Page(s) 12562)

The 1/4 sec. cor. of secs. 13 & 24, determined from the OBTs as follows:

- A dead & fallen Hemlock, 24" dia., bears N.5°E., 14 lks., with blaze healed. I open blaze & uncover scribe marks 1/4 S BT on decayed face of blaze.
- A Cedar, 33" dia., bears S.18°W., 42 lks., with partial scribe marks visible on charred face of blaze.

At corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked: 1/4 $\frac{S\ 13}{S\ 24}$
1954

from which new BTs,

- A Fir, 20" dia., bears N.37°45'E., 50 lks., mkd: 1/4 S13 BT.
- A Cedar, 23" dia., bears S.34 1/4°W., 22 lks., mkd: 1/4 S24 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April/May 1968 - C.S. File 54/67

Found - 1954 GLO brass cap, bent over. Straighten & reset. Orig 33" Cedar, now burned out stump S.18°W. 27.7 ft
1954, 23" Cedar, now burned snag, S.34 1/4°W., 14.5 ft., scribe visible on burned blaze. Rescribed "1/4 S24 CS BT"

New BT - 7" Hemlock N.29°W., 78.3 ft. mkd: 1/4 S13 CS BT.
No live trees S. of corner which lies on gentle slope in logged area.

continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias	Description

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20740)

The ¼ sec. cor. of secs. 13 & 24, monumented with an iron post, 1" dia., firmly set, projecting 8" above the ground, with brass cap (properly) mkd. from which the remains of an original bearing tree
A cedar stump, 33" dia., bears S.18°W., 27.7 ft., with illegible scribe marks visible on partially healed blaze.
and the remains of bearing trees mkd. by Lytle, et. all
A root hole, bears N.37¾°E., 33.0 ft., with down fir alongside, 20" dia., with a healed blaze.
A cedar snag, 23" dia., bears S.34¼°W., 13.6 ft., with scribe marks ¼ visible on open and burned face. (Record, 14.5 ft.)
and new bearing trees
A fir, 12" dia., bears S.70¼°W., 26.9 ft., mkd. ¼ S24 BT.
A fir, 11" dia., bears N.13½°W., 12.7 ft., mkd. ¼ S13 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2115, surveyed January/May 2007 (DCSO records Vol. 56 Page(s) 22062-3)

The ¼ sec. cor. of secs. 13 and 24, monumented with an iron post, 1" dia., firmly set, projecting 9" above ground, in a tractor front tire collar, with brass cap (properly) mkd. from which the remains of an original bearing tree
A burned cedar stump, 33" dia., bears S.18°W., 27.7 ft., no marks visible.
and the remains of the BTs mkd. by Lytle, et al., in 1952-54
A roothole bears N.37¾°E., 33.0 ft., alongside of which is a down fir stump, 20" dia., no marks visible.
A roothole bears S.34¼°W., 13.6 ft., with a down decayed cedar snag, size indeterminate, alongside with no scribe marks visible on burned partially healed blaze.
and bearing trees mkd. by Graham in 1999-2000
A fir, 13" dia., bears S.70¼°W., 26.9 ft., with a healed blaze.
A fir, 13" dia., bears N.13½°W., 12.7 ft., with a healed blaze.