TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 12 & 13

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. P. Wright, Deputy Surveyor, under contract #486, dated Aug. 1, 1883 - (DCSO recs. Vol. 2 Page(s) 844-5)

Set post 4" dia., 4 ft. long with marked stone 12" in ground for ¼ sec. cor. marked ¼ on N face from which:
Fir, 5" dia., bears N.41°W., 38 lks., mkd: ¼ S BT.
Fir, 10" dia., bears S.2°W., 26 lks., mkd: ¼ S BT.

BLM dependent resurvey by Marvin J. Lytle, Palmer Norseth, Thomas A. Tillman, Raymond M. Bicknell, Joseph S. Gawron, and Hans W. Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO recs. Vol. 30 Pg 12564)

Point for the ¼ sec. cor. of secs. 12 & 13, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft long, 1" dia., 28" in the ground with brass cap marked:

¼ S 12 / S 13 1954

from which
A Hemlock, 16" dia., bears N.39°E., 48 lks., mkd: ¼ S12 BT
A Cedar, 8" dia., bears S.39°W., 43 lks., mkd: T21S R8W S13 BT.

Les Roberts - For: International Paper Co. - June 26, 1981 - M 88-22

Found - Brass cap (GLO)
13" Cedar bears S.40°W., 28.6 ft. (scar vis.) 1954
27" Hemlock bears N.38½°E., 32.0 ft. (scribe vis.) 1954

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2720, surveyed Aug./Oct. 2013 - (DCSO records Vol. 58 Page(s) 23117-8)

The ¼ sec. cor. of secs. 12 and 13, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.
from which the BTs mkd. by Lytle, et al, in 1952-54
A hemlock, 35" dia., bears N.39°E., 31.7 ft., with a healed blaze.
A cedar, 24" dia., bears S.39°W., 28.4 ft., with a healed blaze.
From the corner
S.89°16'35"W., 15 ft., creek, 3 ft. wide, course N.10°W.