

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-7

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 560)

-
- Set post 4" dia., 4 ft. long, 24" in ground for cor. to secs. 19, 24, 25 and 30, marked T21S S19 on NE.; R7W S30 on SE.; R8W S25 on SW.; S24 on NW. faces, with 4 notches on the N. & 2 notches on S. edges; from which
- A Fir 6" dia., bears N.38°E., 220 lks. dist. mkd. T21S R7W S19 BT.
 - A Fir 24" dia., bears S.52°E., 50 lks. dist. mkd. T21S R7W S30 BT.
 - A Fir 30" dia., bears S.25°W., 46 lks. dist. mkd. T21S R8W S25 BT.
 - A Fir 30" dia., bears N.42°W., 80 lks. dist. mkd. T21S R8W S24 BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12550-51)

-
- Point for the sec. cor., determined from the remaining original bearing trees:
- A Fir stump bears S.54½°E., 50 lks. dist. (Rec. brg. S.52°W.)
 - Root hole of a fallen Fir 40" dia., bears S.25°W., 46 lks. dist.
 - A Fir 52" dia., bears N.42°W., 80 lks. dist. mkd. T21S S24 in bark.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 27" in the ground, with brass cap mkd:

T 21 S
R 8 W R 7 W
S 24 S 19
S 25 S 30
1952

- from which
- A Fir 8" dia., bears N.61°E., 60 lks. dist. mkd. T21S R7W S19 BT.
 - A Fir 15" dia., bears S.42½°E., 26 lks. dist. mkd. T21S R7W S30 BT.
 - A Fir 15" dia., bears S.50½°W., 15 lks. dist. mkd. T21S R8W S25 BT.
 - A Fir 30" dia., bears N.35¼°W., 109 lks. dist. mkd. T21S R8W S24 BT.

Fd. OK, May 30, 1982 by L. Roberts - M 90-21