

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 560)

-----  
Set post 4" dia., 4 ft. long, 24" in ground for ¼ sec. cor. mkd. ¼ S on W. face; from which

A Fir 18" dia., bears N.21°E., 25 lks. dist. mkd. ¼ S BT.

A Fir 12" dia., bears S.50°?., 7 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12551-52)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 12" in the ground to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd:

¼  
S 24 S 19  
1954

from which

A Fir 68" dia., bears S.20°E., 25 lks. dist. mkd. ¼ S19 BT.

A Fir 36" dia., bears N.20½°W., 29 lks. dist. mkd. ¼ S24 BT.