

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T21-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 560-61)

Set post 4" dia., 4 ft. long, 24" in ground for cor. to secs. 13, 18, 19 & 24, mkd. T21S S18 on NE.; R7W S19 on SE.; R8W S24 on SW.; S13 on NW. face, with 3 notches on N. and 3 on S. edge; from which

A Hemlock 8" dia., bears N.25°E., 29 lks. dist. mkd. T21S R7W S18 BT.

A Fir 5" dia., bears S.28°E., 43 lks. mkd. T21S R7W S19 BT

A Dogwood 6" dia., bears S.9°W., 25 lks. dist. mkd. T21S R8W S24 BT.

A Fir 6" dia., bears N.60°W., 24 lks. dist. mkd. T21S R8W S13 BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12552)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, and in a small mound of stone to top, with brass cap mkd:

T 21	S
R 8 W	R 7 W
S 13	S 18
S 24	S 19
1954	

from which

A Fir 20" dia. bears N.47°E., 36 lks. mkd. T21S R7W S18 BT

A Fir 8" dia. bears S.34½°E. 21 lks. mkd. T21S R7W S19 BT

A Hemlock 8" dia., bears S.71°W., 45 lks. dist. mkd. T21S R8W S24 BT.

A Fir 22" dia., bears N.10½°W., 43 lks. dist. mkd. T21S R8W S13 BT.

Fd. OK and tied in BLM resurvey by Donald R. Beck, Cadastral Surveyor, under Group #655, surveyed Sept/Oct. 1967 - (DCSO records Vol. 34 Page(s) 14165)

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #1000, surveyed May 1999/April 2000 - (DCSO rec. Vol. 54 Page(s) 20737-8)

The cor. of secs. 13, 18, 19, & 24, on the E. bdy of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 14" above the ground, with brass cap (properly) mkd.

continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which the remains of BTs mkd. by Lytle, et. all
A fir stump, 24" dia., bears N.47°E., 23.8 ft., with a healed blaze.
A fir, 19" dia., bears S.34½°E., 13.9 ft., with a healed blaze.
A hemlock, 18" dia., bears S.71°W., 29.7 ft., with a healed blaze.
A fir, 38" dia., bears N.10½°W., 28.4 ft., with a healed blaze.
and a new bearing tree
A hemlock, 17" dia., bears N.87½°E., 15.4 ft., mkd. T21S R7W S18 BT.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21652)

The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 15" above ground, in a collar of stone, with brass cap (properly) mkd.
from which the remains of the BTs mkd. by Lytle, et al. in 1952-54
A fir stump, 21" dia., bears N.47°E., 23.8 ft., with a healed blaze.
A fir, 21" dia., bears S.34½°E., 13.9 ft., with a healed blaze. Tree has a significant northerly curve.
A hemlock, 19" dia., bears S.69¾°W., 27.0 ft., with a healed blaze. (Record, S.71°W., 29.7 ft.)
A fir, 35" dia., bears N.10½°W., 28.4 ft., with a healed blaze. (Record, 38" dia.)
and a bearing tree mkd. by Graham in 1999-2000
A hemlock, 18" dia., bears N.87½°E., 15.4 ft., with a healed blaze.

Fd. USBLM BCIP by T Hostetter, 7/2019 - C.S. File 65/103-9