

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T21-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 561)

Set post 4" dia., 4 ft. long, 24" in ground for ¼ sec. cor., marked ¼ S on W. face; from which

A Hemlock 12" dia., bears S.81°E., 13 lks. dist. mkd. ¼ S BT.

A Hemlock 12" dia., bears S.29°W., 18 lks. dist. mkd. ¼ S BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12553)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

 ¼
 S 13 | S 18
 1954

from which

A Hemlock 24" dia., bears S.73½°E., 45 lks. dist. mkd. ¼ S18 BT.

A Hemlock 14" dia., bears N.34°W., 77 lks. dist. mkd. ¼ S13 BT.

Tony Hostetter - For: Roseburg Resources - July 2019 - C.S. File 65/103-9

Found - 1954 BLM brass cap as described in DCSO Vol. 30, PG. 12553. FROM WHICH;

24" Hemlock stump, 1954 BT, bears; S.73½°E, 29.70 ft to center.

24" Hemlock, 1954 BT, bears; N.34°W., 50.8 ft to center.

New BTs- 12" Fir, marked "X", BT tag, bears; N.30°26'E., 12.8 ft to spike

13" Maple, marked "X", BT tag, bears; S.01°E., 27.0 ft to spike

6" Fir, marked "X", BT tag, bears; N.24°34'W., 13.5 ft to spike.