

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Laban H. Wheeler, Under Contract #467 dated April 7, 1883 (DCSO records Vol. 2 Page(s) 562)

-----  
Set post 4" dia., 4 ft. long, 24" in ground for cor. to secs. 1, 6, 7 and 12, marked T21S S6 onNE.; R7W S7 on SE.; R8W S12 on SW.; S1 on NW. faces, with 1 notch on N. & 5 on S. edges, from which

- A Hemlock 5" dia., bears N.30°W., 23 lks. dist. mkd. T21S R8W S1 BT.
- A Hemlock 8" dia., bears N.60°E., 50 lks. dist. mkd. T21S R7W S6 BT.
- A Hemlock 6" dia., bears S.65°E., 11 lks. dist. mkd. T21S R7W S7 BT.
- A Fir 40" dia., bears S.64°W., 33 lks. dist. mkd. T21S R8W S12 BT.

BLM Resurvey by Lytle; Norseth; Tillman; Bicknell; Gawron and Thielsen, Cadastral Engineers, under Group #304, Surveyed Aug. 1952/Oct. 1954 - (DCSO records Vol. 30 Page(s) 12555)

-----  
Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 21 S	
R 8 W	R 7 W
S 1	S 6
S 12	S 7
1954	

from which

- A Fir 22" dia., bears N.11°E., 12 lks. mkd. T21S R7W S6 BT
- A Fir 27" dia., bears S.1½°E., 34 lks. mkd. T21S R7W S7 BT
- A Fir 18" dia., bears S.5°W., 11 lks. mkd. T21S R8W S12 BT
- A Fir 25" dia. bears N.56½°W., 69 lks. mkd. T21S R8W S1 BT

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2720, surveyed Aug./Oct. 2013 - (DCSO records Vol. 58 Page(s) 23117)

-----  
The cor. of secs. 1, 6, 7, & 12, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 3 ins. above ground, with a brass cap (properly mkd. from which the remains of the BTs mkd. by Lytle, et al, in 1952-54

- A fir, 34" dia., bears N.11°E., 7.9 ft., with axe marks visible.
- A roothole bears S.1½°E., 1.3 ft., alongside of which is a down fir, size indeterminate, with no marks visible. (Record, 22.4 ft.)

continued next page

TOWNSHIP 21 RANGE 08 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 37" dia., bears N. 56½°W., 45.5 ft., with a healed blaze.  
and new bearing trees  
A fir, 14" dia., bears S. 2¼°W., 28.8 ft., mkd. T21S R7W S7 BT.  
A fir, 19" dia., bears S. 77¾°W., 29.2 ft., mkd. T21S R8W S12 BT.  
A fir, 16" dia., bears N. 50°W., 37.1 ft., mkd. T21S R8W S1 BT.  
Alongside is a rebar, 1/2" dia., projecting 3 ft. above ground.  
NAD 1983 (2011)  
Latitude: 43°45'43.41"N.      Longitude: 123°34'58.74"W.