

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 901)

Set Fir post 4½ ft. long, 5" sq., 24" in the ground on steep hill side sloping W. for cor. to Tp. 21 S R 9 and 10 W., marked T21S S31 on the NE.; R9W on the SE.; R10W on the SW.; and S36 on the NW. faces with 6 notches on the N, E, S and W edges, from which

- A Fir 6" dia., bears N.33°30'E., 29 lks. dist. mkd. T21S R9W S31 BT.
- A Fir 8" dia., bears S.53°30'E., 18 lks. dist. mkd. T22S BT.
- A Fir 5" dia., bears S.9°W., 25 lks. dist. mkd. T22S BT.
- A Fir 4" dia., bears N.58°15'W., 14 lks. dist. mkd. T21S R10W S36 BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, Cadastral Engineers; Elmer Strickler, U.S. Surveyor and Gerald A. Sorrels, U.S. Transitman, under instructions dated April 24, 1917 - (surveyed 1919) - (DCSO records Vol. 3 Page(s) 987 (duplicate page #1022))

At the old cor. of Tps. 21 S., Rs. 9 and 10 W., which is a badly decayed post, marked and witnessed as described by the surveyor general, except the NW. bearing tree is dead and fallen.

Alongside the old cor. set an iron post, 3 ft. long, 3" dia., 24" in the ground, for cor. of Tps. 21 S., Rs. 9 and 10 W., on the N. bdy. of T22S R9W, with brass cap mkd:

T21S
R10W R9W
<u>S36 S31</u>
1919

from which

- A Fir 16" dia., bears N.46°E., 27 lks. dist., marked T21S R9W S31 BT. (Old BT)
- A Fir 10" dia., bears N.19°W., 48 lks. dist. mkd. T21S R10W S36 BT. (New BT)

BLM resurvey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16031)

The cor. of Tps. 21 S., Rs. 9 and 10 W., monumented with an iron post, 3" dia., firmly set, projecting 6" above ground, with 1919 brass cap. (Cont. Next Page)

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees:
A decayed Fir stump, size indeterminate, bears N.19°E., 32 lks. dist., no marks visible. (Rec. N.46°E., 27 lks.) and a bearing tree mkd. by Mensch, etal in 1919:
A Fir 28" dia., bears N.46°W., 48 lks. dist., with healed blaze. (Rec. N.19°W.)
and new bearing trees:
A Fir 10" dia., bears N.29°E., 55 lks. dist. mkd. T21S R9W S31 BT.
A Fir 20" dia., bears N.89°W., 60 lks. dist. mkd. T21S R9W S36 BT.