

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 2 Page(s) 903)

Set sandstone 12x8x8 ins., 8" in the ground on steep hill side sloping N. for ¼ sec. cor. mkd. ¼ S on W. face, from which

A Fir 30" dia., bears N.76°E., 29 lks. dist. mkd. ¼ S BT.
A Cedar 20" dia., bears S.60°15'W., 43 lks. dist. mkd. ¼ S BT.

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 987-88) and (dup. Pg. 1022)

Intersect the old ¼ sec. cor., which is a decomposed sandstone mkd. and witnessed as described by the surveyor general. I change this cor. to refer to sec. 31 only and alongside the old cor. set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ sec. cor. of sec. 31 only, with brass cap mkd:

¼
| S 31
1919

from which

A Cedar 34" dia., bears N.7°E., 81 lks. dist. mkd. ¼ S31 BT. (New BT)
A Fir 30" dia., bears S.76°E., 29 lks. dist. mkd. ¼ S31 BT. (Old BT)

Survey by Harvey Wilcox, LS #2244 - For: Stuntzner Eng. - Sept. 5, 1990 - C.S. File 63/104-25

Found - 1" Iron pipe with 2½" brass cap. I.P. had rusted in two at ground level. (1919 GLO B.C.)
58" Cedar with axe marks bears N.07°E., 47.94 ft. to side center.

A stump hole where Fir BT was blown out of and slid down hill, bears S.76°E., 19.14 ft. to center of hole.

Set a 2" alum. cap on a 3/4" x 30" I.Rod along side old monument. Cap mkd: Stuntzner Eng. T21S R9W | S 31 W ¼ 1990 LS 2244.

New BTs- A 56" Cedar with face scribed "W¼ S31 BT" and tag bears S.25°E., 52.93 ft. to a spike in side center.

(Cont. Next Page)

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 31 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 58" Cedar with face scribed W $\frac{1}{4}$ S31 BT and tag bears N.07°E., 47.94 ft. to a spike in side center.
13" Alder with bark scribe W $\frac{1}{4}$ S31 BT and tag bears S.62°E., 24.8 ft. to a spike in side center.
9" Hemlock with face scribed BT X at breast height and tag bears S.58°E., 32.23 ft. to a spike in side center.
About 2 miles up Wells Creek take spur to the West about 1 mile to point where road crosses line between secs. 31 & 36.