

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 100224

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 only, T21-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 989) and (Dup. Pg. 1024)

Set an iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 25 & 36, with brass cap mkd: T21S
S 25
S 36
R10W
1919

from which
A Fir 9" dia., bears S.56°W., 35 lks. dist. mkd. T21S R10W S36 BT.
A Fir 32" dia., bears N.65°W., 88 lks. dist. mkd. T21S R10W S25 BT.

Survey by Les Roberts, LS #1039 - For: I.P. Co. - Dec. 1989 -C.S. File 63/102 and M 109-42

Found - 1919 GLO brass cap with pipe broken off.
38" Fir N.65°W., 58.5 ft., scar visible. (1919 BT, rec. N.65°W., 58.1 ft.)
20" Hemlock N.81°W., 20.8 ft., scribe visible. (No record)
Set 3/4" x 36" alum. rod with a 3/4" alum. cap beside broken pipe. Buried purple magnetic marker beside 36" alum. rod.
Set 72" alum. post with land survey monument sign bolted to, beside alum. cap.
New BTs- 16" Hemlock S.42°E., 41.5 ft., scribed/painted red.
19" Hemlock S.69°W., 6.7 ft., scribed/painted red.
Cor. falls on NE. slope about 125 ft. North of ridge. Ridge bears N.35°W. and S.35°E.