

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 100266

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only, T21-10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 990) and (Dup. Pg. 1026)

Set an Iron post 3 ft. long, 1" dia., 26" in the ground for sec. cor. of sec. 25 only, with brass cap mkd: $\frac{1}{4}$
S 25 |
1919

from which
A Hemlock 16" dia., bears S.20°W., 53 lks. dist. mkd. $\frac{1}{4}$ S25 BT.
A Fir 12" dia., bears N.65°W., 50 lks. dist. mkd. $\frac{1}{4}$ S25 BT

Douglas Co. Surveyors Office - John M. Powell, and crew - March 28, 1973 - C.S. File 56/25-7

Found - 1919 GLO brass cap at $\frac{1}{4}$ corner.
16" Hemlock, now down, S.20°W., 35.0 ft.
12" D.Fir now 39", N.65°W., 33.0 ft., shows good scar.
New BT - 8" Hemlock N.44°W., 34.8 ft. scribed $\frac{1}{4}$ S25 CS BT.

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-8

Found - 1919 GLO brass cap broken off 1" iron pipe. From which:
26" Fir, face evident, sheet metal on top of stump, bears; S65°28'W, 29.3 ft to center (REC: N.65°W., 33.0 ft to center).
14" Hemlock stump, no marks, bears; N.42°37'W., 39.2 ft to center (rec: N.44°W., 34.8 ft to center).
New BTs- 9" Fir, marked "X", BT tag, bears; S.4°05'W., 11.0 ft to spike.
16" Fir, marked "X", BT tag, bears; S.53°00'W., 16.3 ft to spike.
10" Fir, marked "X", BT tag, bears; N.45°37'W., 21.2 ft to spike.
15" Fir, marked "X", BT tag, bears; N.02°23'W., 8.1 ft to spike.