

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 100428

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, T21-10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by Fred Mensch, Charles M. Collier and Fred W. Rodolf, U.S. Cadastral Engineers; Elmer F. Strickler, U.S. Surveyor, and Gerald A. Sorrels, U.S. Transitman, under Instructions dated April 24, 1917 (surveyed 1919) - (DCSO records Vol. 3 Page(s) 994) and (Dup. Pg. 1029)

-----  
Set an Iron post 3 ft. long, 2" dia., 24" in the ground for cor. of secs. 13 & 24, with brass cap mkd:

T21S  
S13  
S24  
R10W  
1919

from which

An Alder 8" dia., bears S.83½°W., 35 lks. dist. mkd. T21S  
R10W S24 BT.

A Fir 36" dia., bears N.52°W., 17 lks. dist. mkd. T21S  
R10W S13 BT.