TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 137100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T22-9

Alias Description
Alias Description
Alias Description
Alias Description

BLM survey by Harvey Wofford; Wayne Rogers and Owen Chatters II, Cadastral Surveyors under Group #'s 811 and 1000 - surveyed Aug. 1973/Oct. 1979 - (DCSO records Vol. 40 Page(s) 16030-31)

Point for the ¼ sec. cor. of sec. 6 only, at proportionate distance.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

¼ S 6
T 22 S R 9 W
1974

from which
A Fir 19" dia., bears S.56¼°E., 56½ lks. dist. mkd. ¼ S6 BT.
A Fir 16" dia., bears West, 95 lks. dist. mkd. ¼ S6 BT.

BLM Sec. Subd. survey by Stephen J. Malloy and John P. Farnsworth, Cadastral Surveyors, under Group #'s 1125 and 1226, surveyed Nov./Dec. 1982 - (DCSO records Vol. 47 Page(s) 17945)

CORNER REPORT
The ¼ sec. cor. of sec. 6 only, on the N. bdy. of the tp., (T22-9) monumented with an iron post, 2½" dia., firmly set, projecting 8" above the ground, with 1974 brass cap.
from which the bearing trees mkd. by Wofford, Rogers and Chatters:
A Fir 20" dia., bears S.57 3/4°E., 56½ lks. dist. with a healed blaze. (Rec. S.56¼°E.)
A Fir 16" dia., bears S.59½°W., 95 lks. dist. with a healed blaze. (Record, West)