

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 969)  
-----  
Set Hemlock post, 5 ft. long, 5" sq., 24" in the ground for 1/4 Sec. cor. mkd. 1/4 S on the N face, from which  
    A Fir, 57" dia., bears S.17°E., 61 lks., mkd: 1/4 S BT.  
    A Fir, 6" dia., bears N.3°15'W., 14 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John Powell - 9/30/1971 - C.S. File 53/66-136  
-----  
Line from 29, 30, 31, & 32 very brushy area logged. (No luck)

Les Roberts, L.S. #1039 - For: I.P. Co. - 12/1989 - C.S. File 63/102 & M 109-42  
-----  
Set - 3/4"x36" finned alum. rod with 3 1/4" alum. cap. Buried purple magnetic marker beside 36" alum. rod. Set 72" alum. post with land survey monument sign bolted to, beside alum. cap.  
    10" Alder, S.58°W., 6.6 ft. bark scribed/painted red.  
    10" Hemlock, N.57°W., 16.2 ft. scribed/painted red.  
    10" Alder, N.3°E., 18.0 ft. bark scribed/painted red.  
    11" Alder, S.31°E., 21.8 ft. bark scribed/painted red.  
Corner lies on SE slope about 200 ft. East of ridge. Ridge bears S.45°W., & N.45°E.