

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 972)</p> <p>-----</p> <p>Set Hemlock post, 5 ft. long, 4" sq., 24" in the ground for ¼ Sec. cor. mkd. ¼ S on the N face, from which</p> <p>    A Fir, 27" dia., bears N.42°E., 15 lks., mkd: ¼ S BT.</p> <p>    A Fir, 26" dia., bears S.18°E., 25 lks., mkd: ¼ S BT.</p>
<p>Eugene M. Wobbe, L.S. #1093 - For: International Paper Co. - March 1983 - C.S. File 58/281-2</p> <p>-----</p> <p>Found - Fir stump bears S.18°E., 16.5 ft. "BT" visible. 1894 Stump hole bears N.42°E., 9.9 ft. 1894</p> <p>Set - 1¼"x36" IP with a 2½" B.C. mkd: ¼ S19 S30 T21S R9W. 6" Fir bears N.24°E., 11.2 ft., scribed. 7" Hemlock bears S.9°E., 8.5 ft., scribed.</p>
<p>Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-8</p> <p>-----</p> <p>Found - 1983 brass cap as set by Wobbe (C.S. file 58/281) from which: Fir stump obt, bears; S.18°E., 16.5 ft to center. 7" Hemlock stump, Wobbe BT, bears; S.09°E., 8.5 ft to center.</p> <p>New BTs- 52" Fir, marked "X", BT tag, bears N.84°E., 26.0 ft to spike. 36" Fir, marked "X", BT tag, bears N.46°W., 15.2 ft to spike.</p>
<p> </p>