

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 6 only, South

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Jerry Estabrook - For: Roseburg Resources - 1/2022 - M180-48

The record monument for the S¼ corner of section 6 only could not be found due to a land slide at the corner location, leaving an exposed rock face at the corner position. I therefore reset the corner monument at a distance/distance intersection from the record BTs holding the record distances from the BTs.
Fd BTs - A 42" Fir with healed face bears N.52°E., 117.5' placed new tag on BT.
 A 36" Fir with healed face bears N.72°W., 47.4'. placed new tag on BT
Set - A 5/8"x6" iron rod with plastic cap mkd: "ESTABROOK LS2703" in rock face.
New BTs- A 26" Fir, face scribed "X BT" with X-chop and tag bears S.42°E., 82.2' to a spike at side center
 A 16" Alder, bark scribed "X BT" with X-chop and tag bears S.4°W., 55.7' to a spike at side center
B0 set - A steel fence post bears West 7.0'.
Lat and Long per GARMIN ETREX hand held GPS:
N: 43°46'02.3" W: 123°49'09.5"