

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 967)

Set Fir post 5 ft. long, 5" sq., 24" in the ground on hill side sloping SE for 1/4 sec. cor., from which
 A Fir, 36" dia., bears N.48°E., 37 lks., mkd: 1/4 S BT.
 A Fir, 40" dia., bears N.44°W., 129 lks., mkd: 1/4 S BT.

Douglas Co. Surveyors Office - John Powell - W. Penley - J. Heritage - Sept. 28, 1971 - C.S. File 53/66-124

Found - 36" D.Fir, now stob, N.48°E., 24.4 ft. opened earlier for scribe "BT"
 40" D.Fir now stump hole, N.44°E., 85.1 ft.
Set - Brass cap at cor. mkd: County Surveyor's Office 1971 T21S 1/4 S31|S32 R 9 W
 14" D.Fir N.10°W., 13.5 ft., mkd: 1/4S31 CS BT
 7" D.Fir S.43°E., 18.5 ft., mkd: 1/4S32 CS BT
Note - Call of 1 chain to top spur hits good. Road approx. 50 ft. West of road.