

PRIMARY CORNER DESCRIPTION 1/4 Secs. 29 & 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 970)  
-----  
Set Hemlock post, 4½ ft. long, 4" sq., 24" in the ground on steep hill side sloping N for ¼ Sec. cor. mkd. ¼ S on the W face, from which  
    A Hemlock, 16" dia., bears N.79°E., 29 lks., mkd: ¼ S BT.  
    A Fir, 40" dia., bears S.41°E., 15 lks., mkd: ¼ S BT.

Eugene M. Wobbe, L.S. #1093 - For: International Paper Co. - March 28, 1983 - C.S. File 58/281  
-----  
Found - Fir stump bears S.41°W., 9.9 ft. with "¼ S BT" visible on the NE face. Rec. is S.41°E.  
        Stump hole bears N.79°E., 19.1 ft.  
Set - 1¼" x 36" IP with a 2½" BC mkd: ¼ S29 S30 T21S R9W  
      12" Fir bears S.40°E., 13.2 ft. (scribed)  
      6" Hemlock bears N.89°W., 8.8 ft. (scribed)

BLM Dependent resurvey by Joseph M. Mannix, Cadastral Surveyor under Group No. 2721, surveyed June/Aug. 2013 - (DCSO records Vol. 58 Page(s) 23172)  
-----  
The ¼ sec. cor. of secs. 29 and 30, perpetuated by Wobbe, in 1983; monumented with an iron post, 1¼" dia., firmly set in concrete, with top flush with the surface of the ground, with a brass cap (properly) mkd.  
from which the remains of an original bearing tree  
    A decayed fir stump, 38" dia., bears S.41°W., 9.9 ft., with scribe marks ¼ S BT visible on open blaze.  
    (Record, S.41°E.)  
and the remains of the bearing trees mkd. by Wobbe  
    A fir, 23" dia., bears S.42½°E., 13.2 ft., with a healed blaze.  
    A root hole bears N.89°W., 8.8 ft., alongside of which is a down hemlock, size indeterminate, with no marks visible and a metal tag.  
and a new bearing tree  
    A maple, 13" dia., bears N.40°E., 10.5 ft., mkd. ¼ S29 BT on bark.  
No suitable trees in sec. 30.  
Alongside the cor. is an iron rod, 1/2" dia., projecting 3 ft. above ground.