

TOWNSHIP 21 RANGE 09 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608, dated April 17, 1893 - (DCSO rec. Vol. 2 Page(s) 973)

-----  
Set Alder post 4" sq., 4½ ft. long, 24" in the ground on steep hill side sloping NW for ¼ Sec. cor. mkd ¼ S on the W face, from which

A Hemlock, 22" dia., bears S.8°E., 50 lks., mkd: ¼ S BT.

A Fir, 30" dia., bears S.10°W., 38 lks., mkd: ¼ S BT.

BLM dependent resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #350 & 511, surveyed April 1966/May 1967 - (DCSO records, Vol. 34 Page(s) 14265-6)

-----  
The ¼ sec. cor. of secs. 19 & 20 determined at the record bearing & distance from the orig. BTs:

A Hemlock, 42" dia., bears S.8°E., 15 lks., with fragmentary scribe marks visible on partially healed blaze. (Rec. 50 lks.)

A root hole of a fallen Fir, 52" dia., bears S.10°W., 38 lks., with healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

¼  
S 19|S 20  
T 21 S|R 9 W  
1967

from which a new BT

A Hemlock, 15" dia. bears N.45°W., 42 lks., mkd: ¼ S19 BT.